

ZNR-421

32-Channel 4-Bay 1U Rackmount Standalone NVR



- 32 channels, 32 Free Licenses
- 4 Storage Bay(s)
- Rack Space: 1U, Rackmount Standalone NVR
- Embedded Linux
- Hi3536
- Digital Input/Output
- Web Client

► Specifications

Product Profile

Product Type	Standalone NVR
Maximum Resolution	12MP
Maximum Number of Video Devices	32
Maximum Number of Clients	Local: 1, Remote: 2

Hardware

CPU	Hi3536
-----	--------

License

License required	No
Free License	32

Live View

Digital Zoom	Yes
Event Status	Display event status upon alarm or upon connection loss or recovery between server and client
Instant Playback	Instant Playback in live view window

PTZ

PTZ Control	PTZ Control, Speed Control
-------------	----------------------------

Video

Compression	H.265, H.264
Maximum Frame Rate vs. Resolution	20 fps at 4072 x 3076 30 fps at 3840 x 2160 20 fps at 2688 x 1520 25 fps at 1920 x 1080 25 fps at 1280 x 720

Audio

Audio Type	2-way, Line-in, Line-out
------------	--------------------------

Network

Ethernet Port	Total ports: 2 port(s) Non-PoE: 2 port(s), Ethernet (10/100/1000 Base-T), RJ-45 connector
---------------	---

Recording

Scheduled Recording	Yes
Event Recording	Yes
Manual Recording	Yes
Maximum Recording Throughput	320 Mbps

Search & Playback

Playback Control	Continuous forward and backward playback with speeds 1/8x, 1/4x, 1/2x, 1x, 2x, 4x, 8x, 16x, 32x, 64x, 128x, 256x, pause, stop
Synchronized Playback	16 channels
Video Export	MP4

Event

Event Trigger	[Video Device]: Video motion detection, External device through digital input, Sound detection, Intelligent event detection (Intrusion Detection, Tampering Detection)
---------------	--

System

Permission control	128 Remote users, Customizable permissions for user groups
Server Operating System	Embedded Linux
Client PC Operating System	Windows 7, Windows 8, Windows 10
USB	2-Port USB 2.0, 1-Port USB 3.0
Language	English

Integration

ONVIF Compliant	Yes
Web Browser	IE 10 or newer

Storage

Storage Bay	SATA, Max. 4 Disk(s)
Maximum Recording Capacity	10TB x4
RAID Level	No

Interface

Digital Input/Output	16/4
Local Access	HDMI/VGA monitor, USB Mouse


General

Power Source	DC 12V
Power Consumption	12 W (DC)
Weight	3140g (6.92lb)
Dimensions	(W x H x D): 440mm x 44mm x 344mm (17.3" x 1.7" x 13.5") Rack Space: 1U
Operating Temperature	-10°C ~ 55°C (14°F ~ 131°F)
Operating Humidity	10% - 90% RH, non-condensing
Remote Access	Web Client
Approvals	CE, FCC, EAC, BSMI
Warranty	2 Year(s). For extended warranty offering, see http://www.acti.com/support/warranty

The product is for exporting only. Not apply to domestic orders (Taiwan).







► Related Products

Mounting Accessories - Standalone NVR Mount

PMAX-1205	 Rack Bracket for ZNR-421
-----------	--

Note: Some mounting accessories may need additional accessories for installation. Please check www.acti.com/mountingselector for more information.

Network & Storage Peripherals - Hard Disk

PHDD-2200	 WD WD1005FBYZ 1TB 3.5" Hard Disk Drive, 7200 RPM 128 MB Cache (for ENR-0x0P, ENR-110, ENR-120, ENR-130, ENR-22x, ENR-22xP, GNR-310, GNR-320, INR-100, INR-340, INR-430, INR-440, INR-450, INR-460)
PHDD-2301	 HGST ULTRASTAR 7K6000 2TB 3.5" Hard Disk Drive, 7200 RPM 128MB Cache (for ENR-1xx, ENR-0x0P, ENR-22x, ENR-22xP)
PHDD-2500	 WD WD40PURX 4TB 3.5" Hard Disk Drive for Data Storage (for ENR-110, ENR-120, ENR-130, ENR-140, ENR-190, ENR-1xxx, GNR-3000, INR-310, INR-320, and INR-330)
PHDD-2501	 HGST ULTRASTAR 7K6000 4TB 3.5" Hard Disk Drive, 7200 RPM 128MB Cache (for ENR-1xx, ENR-0x0P, ENR-22x, ENR-22xP)
PHDD-2700	 WD WD60PURX 6TB 3.5" Hard Disk Drive - 6000 RPM 64MB Cache for Data Storage (for ENR-110, ENR-120, ENR-130, ENR-140, ENR-190, GNR-3000, INR-310, INR-320, and INR-330)
PHDD-2702	 WD Ultrastar 6TB 3.5" Hard Disk Drive, 7200 RPM 256MB Cache

Other Accessories - Accessory Part

R704-X0000



SATA Power Cable (for ZNR series)