

Z950

2MP 20x Outdoor PTZ with IR LED 150m, WDR 120dB



- 2 Megapixel, 20x, PTZ
- IR LED 150m, Superior WDR (120 dB)
- Color Min. Illumination 0.001 lux
- 360° endless
- Weatherproof (IP66), Vandal proof (IK10), UL Listed

► Specifications

Product Profile

Product Type	PTZ
Application Environment	Outdoor
Maximum Resolution	2MP
Image Sensor	Progressive Scan CMOS
Sensor Size	1/2.8 "
Day / Night	Yes
Low Light Sensitivity	Superior
Minimum Illumination	Color: 0.001 lux at F1.5 (AGC on); B/W: 0 (IR LED on)
Mechanical IR Cut Filter	Yes
IR LED	Adaptive IR LED
IR Working Distance	150m
Electronic Shutter	1-1/100000 second (manual mode); 1-1/100000 second (auto mode)
S/N Ratio	54 dB

Lens

Focal Length	Zoom, f5.2-104mm
Aperture	F1.5-F3.0

Zoom Ratio	20x optical zoom, 16x digital zoom
Focus	Auto focus
Lens Mount	Board mount
Horizontal Viewing Angle	55.93° - 3.52°
Vertical Viewing Angle	33.25° - 1.98°

PTZ

Manual Panning / Tilting Speed	0.1° - 240°/second, 0.1° - 160°/second
Preset Panning / Tilting Speed	0° - 300°/second, 0° - 240°/second
Panning Range	360° endless
Tilting Range	-15°~90°

Video

Compression	H.265, H.264 (Baseline/ Main/ High profile), MJPEG
Maximum Frame Rate vs. Resolution	30 fps at 1920 x 1080 25 fps at 1920 x 1080 30 fps at 1280 x 720 25 fps at 1280 x 720
Multi-Streaming	Simultaneous triple streams
Digital Noise Reduction	2D + 3D DNR
Wide Dynamic Range	Superior WDR (120 dB)
Image Orientation	Flip, Mirror, Rotation (Corridor mode)
Image Enhancement	Defogging
Privacy Mask	Yes
Text Overlay	Yes

Audio

Audio Type	2-way, Line-in, Line-out
Audio Compression	G.711

Network

Network Protocol & Service	IPv4, TCP, UDP, DHCP, PPPoE, HTTP, HTTPS, DNS, DDNS, NTP, RTP, RTSP, RTCP, SMTP, FTP, IGMP, ICMP, ARP, UPnP, QoS, SNMP, SSL, IEEE 802.1X
Ethernet Port	1 x Ethernet (10/100 Base-T), RJ-45 connector

Event

Event Trigger	Video motion detection, Tampering detection, External device through digital input,
Event Response	Save video to storage, Activate external device through digital output

Integration

ONVIF Compliant	Yes, Profile S, Profile G, Profile T
-----------------	--------------------------------------

Interface

Digital Input/Output	1/1
Operating Button	No


General

Power Source	DC 24V, AC 24V
Power Consumption	42 W (AC, heater and IR on)
Weight	5280g (11.6lb)
Dimensions	(Ø x H): 227mm x 359.4mm (8.9" x 14.2")
Environmental Casing	Weatherproof (IP66), Vandal proof metal casing (IK10)
Corrosion Protection	Optional for project request. Chassis corrosion resistance at the seashore approximately 3 years.
Bundled Accessories	Power Adapter (DC 24V)
Heater	Yes
Operating Temperature	-40°C ~ 65°C (-40°F ~ 149°F)
Operating Humidity	10% - 95% RH, non-condensing
Approvals	CE, FCC, EAC, IP66, IK10 (metal casing), UL Listed
Real-time Clock (RTC)	Yes
Warranty	2 Year(s). For extended warranty offering, see http://www.acti.com/support/warranty

► Photo Indication



► Dimension Diagram



Unit: mm [inch]

Unit: mm [inch]

► Related Products

Mounting Accessories - Camera Mount

PMAX-0115		Pendant Mount (for A950, A951, A952, A956, Z950, Z952)
PMAX-0116		Straight Tube, 200 mm (for Z950)
PMAX-0117		Straight Tube (for Z950, Z952)
PMAX-0322		Wall mount (for Z950, Z952)
PMAX-0358		Parapet Wall Mount (for Z95X, Q84).
PMAX-0404		Corner Mount (for Z950, Z952)
PMAX-0503		Pole Mount (for PMAX-0102, PMAX-0312, PMAX-0313, PMAX-0314, PMAX-0702, PMAX-1106, PMAX-1107), supports 5.25" to 8.5" Poles
PMAX-0513		Pole Mount (for Z950, Z952)
PMAX-0702		Junction Box for PTZ and Dome Cameras
PMAX-0711		Junction box (for Z950, Z952)
PMAX-1403		Ceiling Mount (for Z950, Z952)

Note: Some mounting accessories may need additional accessories for installation. Please check www.acti.com/mountingselector for more information.

Network & Storage Peripherals - Data Switch

PPSW-0102		PLANET FGSD-1011HP 8-Port 802.3at PoE Switch (PoE Budget 120W)
-----------	---	--

Audio Devices - Microphone

PMIC-0100		Active Microphone Omnidirectional for all Cameras with Line-in Audio
-----------	---	--