

# INR-401

## 256-Channel 12-Bay RAID 2U Rackmount Standalone NVR with Redundant Power Supply



- 256 channels, 64 Free Licenses
- 12 Storage Bay(s), Hot Swappable Drive
- Hardware RAID (Add-on Card) 0, 1, 5, 6, 10, 50, 60, SATA, USB
- Rack Space: 2U, Rackmount Standalone NVR
- Redundant Power Supply
- Windows 10 IoT, NVR 3 Corporate
- Intel Core i7-6700
- Audio, HDMI x 2, VGA x 1, DVI x 1 (maximum two ports concurrent use)
- Workstation, Web Client, Mobile Client
- Forensic Search, Event Search, Smart Search, Metadata Search
- Object Visual Tracking
- Multi-Browser Support

### ► Specifications

#### Product Profile

Product Type	Standalone NVR
Maximum Resolution	Support all ACTi cameras in all resolutions
NVR Edition	NVR 3 Corporate
Maximum Number of Video Devices	256
Maximum Number of POS devices	256 (requires additional license)
Maximum Number of Access Control and Network I/O devices	256 (requires additional license)
Maximum Number of Clients	Local: 1, Remote: 5

#### Hardware

System Architecture	x86-based (Intel platform)
CPU	Intel Core i7-6700

**License**

License required	Yes
Free License	64 (64 channels for ACTi and 1 channel for third-party video device)

**Live View**

Display Layout Mode	Local: 1, 3, 4, 5, 6, 8, 9, 10, 12, 16 Remote (IE client): 1, 3, 4, 5, 6, 8, 9, 10, 12, 16, 18, 24, 25, 35, 36, 48, 49, 64 Remote (Lite web client): 1, 3, 4, 5, 6, 8, 9, 10, 12, 16 Remote (Workstation): 1, 3, 4, 5, 6, 8, 9, 10, 12, 16, 18, 24, 25, 35, 36, 48, 49, 64, 81, 100, 121 (11x11), 144 (12x12), 169 (13x13), 196 (14x14), 225 (15x15) ** NVR 3 display grid cells can be merged into different shape and size.
Fisheye Dewarping	Yes (Live View, Playback, Export)
Local Live View performance	Please check "Standalone NVR Performance Validator" ( <a href="http://www.acti.com/SANVRPerformance">http://www.acti.com/SANVRPerformance</a> )
Digital Zoom	Yes
Visual Tracking	Yes (Cross-camera tracking via pre-defined regions)
Event Status	Display event status upon alarm or upon connection loss or recovery between server and client or when the allocated disk space is full
Instant Playback	Instant Playback in live view window
Embedded websites in Live View	Display and connect to pre-configured embedded website

**Map**

e-Map	Yes
Google Map	Yes
Layout	Area maps with camera icons, small live view windows, hyperlinked
Setup	e-Map image upload, Google maps settings and preset management, camera positioning, vision angle and pointed direction of camera, view positioning, source positioning, extended devices for Point-of-sale (POS), Access Control, Network I/O
PTZ Mode	Mouse PTZ mode to control e-Map video streams

**PTZ**

PTZ Control	PTZ Control, Speed Control, 32 preset points
Joystick	USB based joystick supported

**Backup**

Automatic Recording Backup	Yes, Pre-scheduled recording backups using the Backup Server.
----------------------------	---

**Video**

Video Source	ACTi cameras/encoders, ONVIF Cameras, Integrated 3rd-party cameras, Mobile Client, USB/Webcam
Compression	H.265 Adaptive Stream, H.264 Adaptive Stream, MPEG-4, MJPEG
Hardware Accelerated Decoding	Yes (for workstation PC only), H.264, H.265

## Analytics

Analytics from Camera	Receive analytics based events from the cameras and respond to the events: Face Detection; Smart Motion Detection (People Detection, Vehicle Detection); Smart Intrusion Protection (Intrusion Detection, Line Crossing Detection, Enter Area Detection, Exit Area Detection); People Counting (People Line Counting, People Area Counting, People Flow Counting, Crowd Detection); Object Metadata; Object Recognition; Temperature Detection (Fire Detection, Smoking Detection, Smoke Detection, Temperature Measurement); Traffic Monitoring
-----------------------	---

## Audio

Audio Type	2-way, Mic-in, Line-in, Line-out
------------	----------------------------------

## Network

Network Protocol & Service	IPv4/v6, TCP, UDP, DHCP Client, HTTP, HTTPS, DNS, NTP, RTP, RTSP, SMTP, FTP, ICMP, ARP, Bonjour, UPnP, LDAP (client), iSCSI
Ethernet Port	2 x Ethernet (1000 Base-T), RJ-45 connector

## Recording

Scheduled Recording	Yes
Event Recording	Yes
Manual Recording	Yes
Event Speed-up Recording	Yes
Dual Stream Management	Yes
Maximum Recording Throughput	300 Mbps

## Search & Playback

Playback Control	Continuous forward and backward playback with speeds (1/64, 1/32, 1/16, 1/8, 1/4, 1/2, 1, 2, 4, 8, 16, 32, 64, 128, 256) or frame-by-frame, pause, stop
Synchronized Playback	225 channels
Recording Search	Search video recordings by time, events, channels, bookmarks, notifications and listed as clickable time-based thumbnails for full-size view and snapshot download
Event Search	Search within previously recorded AI events
Smart Search	Set ROI and look for the people and vehicles appearing in the ROI in the past recordings (requires cameras with Smart Motion Detection feature)
Forensic Search	Select target object (people, vehicle) and search for the similar object through all the channels
Metadata Search	Select attribute filters (color, gender, age, etc) and find thumbnails matching the criteria
Object Visual Tracking	View thumbnails generated by Forensic Search and playback by time sequence
Video Export	RAW, AVI, MP4, EXE, GPU Hardware accelerated video export supported with AVI format
Snapshot Export	BMP, JPEG, PNG
Embedded Media Player	Yes, supports up to 64 channels view

## Event

Video Push	Support Video Push from ACTi Mobile Client devices
------------	--

<p>Event Trigger</p>	<p>[NVR]: Disk full, Disk not found, Disk is available, S.M.A.R.T. Failure and Normal, Schedule service start and stop, Video Push start and stop, Time Backward, CPU limit exceeded for Server PC, CPU limit exceeded for NVR services, GPU Loading Detection for workstation only, Memory limit exceeded for Server PC and NVR services, Network Send/Receive Limit Exceeded for Server PC.</p> <p>[Video Device]: Video motion detection, Passive IR sensor, External device through digital input, Sound detection, Intelligent event detection, Video Push start and stop, Video loss and recovery, Disk Write Failure and Available.</p> <p>[Access Control Server]: Access Allowed, Access Denied, Access Unknown, Access Expiration, Denied Time Zone, Egress, Duress, Alarm, Arm, Disarm.</p> <p>[Extended Device]: Point-of-sale (POS) status, Network I/O status, Access Control status</p>
<p>Event Response</p>	<p>Pop-up window with live video and event confirmation activation, Switch to hotspot window, Switch to customize view, Command a PTZ device to go to a preset point, Play alert sound, Activate external device through digital output, Execute system command to activate other programs, Upload video or snapshot to FTP server, E-mail notification with snapshots, Push notification, Send LINE notification message</p>

**Redundancy Server**

<p>Redundancy Service</p>	<p>Yes, N-to-N, N+1 (With limited functions when NVR 3 server acts as Redundancy server)</p>
---------------------------	--

**System**

<p>Permission control</p>	<p>Unlimited number of users, Active Directory, Customizable permissions for user groups, Account lockout, Automatic logout after idle, Playback password protected, Password validity period, Password Expiration Notification</p>
<p>Watchdog</p>	<p>Support</p>
<p>Server Operating System</p>	<p>Windows 10 IoT</p>
<p>Client PC Operating System</p>	<p>Windows 7 SP1, Windows 8.1, Windows 10, Windows 11, Windows Server 2008 R2 SP1, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019</p>
<p>Server and Client PC requirements</p>	<p>Please use <a href="https://www.acti.com/pcselector">https://www.acti.com/pcselector</a> For client PC requirements, please check the Performance: Live View section.</p>
<p>Mobile Client Program</p>	<p>Mobile device application (ACTi Mobile Client) supports Live View, PTZ Control, Video Push, Supported device(s) iOS, Android device</p>
<p>USB</p>	<p>5-Port USB 3.0</p>
<p>Language</p>	<p>Multi-Language</p>

**Integration**

<p>Unified Solution</p>	<p>Fully compatible with ACTi cameras, encoders, central management system, TV wall and intelligent video surveillance software</p>
<p>CMS Support</p>	<p>Yes (ACTi CMS 2)</p>
<p>GPS Position</p>	<p>Manual setting</p>
<p>Edge Recording</p>	<p>Automatically restore the lost videos from the memory card of camera to NVR server via ONVIF (Profile G) or proprietary protocol integrations after network connection recovery.</p>
<p>ONVIF Compliant</p>	<p>Profile S, Profile G, Profile T (officially listed as ONVIF conformant at <a href="http://www.onvif.org">www.onvif.org</a>)</p>
<p>Web Browser</p>	<p>IE 11 (Please verify that your computer meets the minimum system requirements for Internet Explorer from Microsoft website.), Lite web client: Microsoft Edge 80.0.361.66 (Normal mode) or newer, Google Chrome 71.0.3578 or newer, Firefox 64.0.2 or newer, Apple Safari 12.0.2 or newer</p>

Third-party Integration	Point of Sale (POS), Access Control, Network I/O, Parking Management Station (PMS), (Various optional integrations requiring additional license)
-------------------------	--

## Storage

Supported Storage Technology	NAS, SAN
System Drive	SSD, 256GB
Storage Bay	SATA, Max. 12 Disk(s) (without storage disks)
Hot Swappable Drive	Yes
HDD Size	3.5"
Maximum Recording Capacity	14TB x12
RAID Level	Hardware RAID (Add-on Card) 0, 1, 5, 6, 10, 50, 60
Supported Storage	Video Recording: SATA disk, Video Exporting: USB

## Interface

Serial Port	1 x RS-485/RS-422
Audio Interface	1/1, 3.5mm Phone Jack
External Storage Interface	iSCSI, USB
Local Access	USB joystick, keyboard & mouse
Local Display Interface	HDMI x 2, VGA x 1, DVI x 1 (maximum two ports concurrent use)

## General

Power Source	AC 100-240V
Redundant Power Supply	Yes, 550W x 2
Weight	16000g (35.274lb)
Dimensions	(W x H x D): 482.6 mm x 87mm x 625mm (19" x 3.5" x 24.61") Rack Space: 2U
Bundled Accessories	Power cord
Mount Type	Rack mounts
Fan	Yes
Operating Temperature	0°C ~ 60°C (32°F ~ 140°F)
Operating Humidity	0% - 95% RH, non-condensing
Remote Access	Workstation, Web Client, Mobile Client
Approvals	BSMI
Color	Silver
Warranty	3 Year(s). For extended warranty offering, see <a href="http://www.acti.com/support/warranty">http://www.acti.com/support/warranty</a>

\*\* The actual maximum number of channels may vary depending on the server/client PC performance and network throughput.

## ▶ Ordering Information

LEXD3000	The license is for network I/O or access control extended device to work on NVR 3 Corporate. The number of add-on devices supported: 1-100. Price listed is for single device add-on license. NVR 3 Corporate: The software NVR with support up to 100 cameras or video encoders; Smart Search; Export video; Event management; e-Map; free license for 1-channel ACTi and 1-channel third-party video devices included; Support for integration with POS, access control and extended device by additional software license.
LPOS3000	The license is for POS device to work on NVR 3 Corporate. The number of add-on devices supported: 1-100. Price listed is for single device add-on license. NVR 3 Corporate: The software NVR with support up to 100 cameras or video encoders; Smart Search; Export video; Event management; e-Map; free license for 1-channel ACTi and 1-channel third-party video devices included; Support for integration with POS, access control and extended device by additional software license.