PMIC-0100



Active Microphone Omnidirectional for all Cameras with Line-in Audio

Specifications

Product Profile

Product Type	Microphone
Description	Active Microphone Omnidirectional for all Cameras with Line-in Audio

Audio

Microphone Type	Active
Transducer Type	Condenser
Frequency Response	300 - 5500 Hz
Impedance	600 ohms
Audio Output Signal	2Vpp/-25dB
Current Consumption	Max. 10mA
Polar Pattern	Omni-Directional

Interface

Audio Interface	3.5mm Phone Jack, Terminal block

General

Power Source	DC 9-12V
Weight	50g (0.06lb)
Bundled Accessories	Power cord, RCA to two wire Converter cable, RCA-to-3.5mm Jack Converter cable
Cable Length	2.3 m

Storage Temperature	-25 °C ~ 85 °C (-13 °F ~ 185 °F)
Warranty	1 Year(s)

Related Products

Box - Fixed Box

A213		5MP Box with D/N, Extreme WDR, ELLS, Fixed lens, f2.8mm/F2.0, Auto Back Focus, H.265/H.264, 2D+3D DNR, Built-in Microphone, PoE/DC12V, DI/DO, RS-485
A29		2MP Box with D/N, Extreme WDR, ELLS, Fixed lens, f2.8mm/F1.8 (HOV:108.6°), Auto Back Focus, H.265/H.264, 1080p/60fps, 2D+3D DNR, Audio, PoE/DC12V, DI/DO, RS-485
E217		2MP Video Analytics Box with D/N, Extreme WDR, SLLS, Fixed lens, f2.93mm/F2.0 (HOV:101.3°), H.264, 1080p/60fps, 2D+3D DNR, Audio, PoE/DC12V, DI/DO, RS-422/RS-485, Built-in Analytics

Box - Zoom Box

B26		3MP Video Analytics Zoom Box with D/N, Extreme WDR, SLLS, 36x Zoom lens, f4.6-165.6mm/F1.55-5.0 (HOV:57.6°-2.35°), DC iris, Auto Focus, H.265/H.264, 2D+3D DNR, Audio, PoE/DC12V, DI/DO, RS-422/RS-485, Built-in Analytics

Bullet - Vari-focal Bullet

E43B		5MP Bullet with D/N, Adaptive IR, Basic WDR, Vari-focal lens, f2.8-12mm/F1.4 (HOV:69.2°-28.2°), H.264, 1080p/30fps, DNR, Audio, PoE, IP68, IK10 (metal casing), DI/DO

Bullet - Zoom Bullet

A415		3MP Zoom Bullet with D/N, Adaptive IR, Extreme WDR, SLLS, 4.3x Zoom lens, f2.8-12mm/F1.4-2.8 (HOV:88°-25°), P-Iris, Auto Focus (for installation), H.265/H.264, 1080p/30fps, 2D+3D DNR, Audio, PoE/DC12V, IP66, IK10 (metal casing), DI/DO
A421		8MP Video Analytics Zoom Bullet with D/N, Adaptive IR, Extreme WDR, SLLS, 4.3x Zoom lens, f2.8-12mm/F1.3, Auto Focus (for installation), H.265/H.264, 4K/30fps, 2D+3D DNR, Audio, PoE/DC12V, IP66, IK10 (metal casing), DI/DO, Built-in Analytics
A422		4MP Zoom Bullet with D/N, IR, Extreme WDR, SLLS, 5x Zoom lens, f2.7-13.5mm/F1.6 (HOV:102.8°-32.4°), H.265/H.264, 3D DNR, Audio, PoE/DC12V, IP68, IK10 (metal casing), DI/DO
A423		6MP Zoom Bullet with D/N, IR, Extreme WDR, SLLS, 4.3x Zoom lens, f2.8-12mm/F1.6 (HOV:102.1°-34.5°), H.265/H.264, 3D DNR, Audio, PoE/DC12V, IP68, IK10 (metal casing), DI/DO
A425		2MP Zoom Bullet with D/N, Adaptive IR, Extreme WDR, ELLS, 4.3x Zoom lens, f2.8-12mm/F1.8-3.3 (HOV:106.6°-34.6°), Adaptive iris, Auto Focus (for installation), H.265/H.264, 1080p/60fps, 2D+3D DNR, Audio, PoE/DC12V, IP67, IK10 (metal casing), DI/DO
A429		4MP Deep Learning AI LightGuard 4.3x Zoom Bullet with IR LED 85m, WDR 150dB

B412		3MP Video Analytics Zoom Bullet with D/N, Adaptive IR, Extreme WDR, SLLS, 10x Zoom lens, f4.7-47mm/F1.6-3.0 (HOV:58°-5.8°), DC iris, Auto Focus, H.265/H.264, 2D+3D DNR, Built-in Microphone, High PoE/DC12V, IP67, IK10 (metal casing), DI/DO, Built-in Analytics
B419		5MP Video Analytics Zoom Bullet with D/N, Adaptive IR, Extreme WDR, SLLS, 10x Zoom lens, f4.7-47mm/F1.6-3.0 (HOV:50.67°-5.14°), DC iris, Auto Focus, H.265/H.264, 2D+3D DNR, Built-in Microphone, High PoE/DC12V, IP67, IK10 (metal casing), DI/DO, Built-in Analytics
I42		2MP Video Analytics Zoom Bullet with D/N, Adaptive IR, Extreme WDR, ELLS, 36x Zoom lens, f4.6-165.6mm/F1.55-5.0 (HOV:62.7°-2.7°), DC iris, Auto Focus, H.264, 1080p/60fps, 2D+3D DNR, Audio, PoE/DC12V, IP67, IK10 (metal casing), DI/DO, Built-in Analytics

Dome - Fixed Dome

A76		4MP Outdoor Dome with D/N, IR, Extreme WDR, SLLS, Fixed lens, f2.8mm/F1.6 (HOV:99°), H.265/H.264, 3D DNR, Audio, PoE/DC12V, IP68, IK10, DI/DO
A77		6MP Outdoor Dome with D/N, IR, Extreme WDR, SLLS, Fixed lens, f2.8mm/F1.6, H.265/H.264, 3D DNR, Audio, PoE/DC12V, IP67, IK10, DI/DO
E918		3MP Outdoor Mini Dome with Superior WDR, Fixed lens, f1.9mm/F2.8 (HOV:126.4° (overview area), 77.1° (high detail area)), H.264, 1080p/30fps, DNR, Audio, PoE, IP68, IK10, EN50155
E936		2MP Video Analytics Outdoor Mini Dome with Extreme WDR, SLLS, Fixed lens, f2.55mm/F2.2 (HOV:110.3°), H.264, 1080p/60fps, 2D+3D DNR, Audio, PoE, IP68, IK10, EN50155, Built-in Analytics
Z91		4MP Outdoor Mini Dome with D/N, Adaptive IR, Extreme WDR, SLLS, Fixed lens, f2.8mm/F2.0 (HOV:101.8°), H.265/H.264, 1080p/30fps, 2D+3D DNR, Audio, PoE/DC12V, IP67, IK10, DI/DO

Dome - Zoom Dome

B64		1.3MP Indoor Zoom Dome with D/N, Adaptive IR, Basic WDR, SLLS, 3x Zoom lens, f3-9mm/F1.2-2.1 (HOV:90.6°-31.8°), DC iris, Auto Focus, H.264, 720p/60fps, DNR, Audio, PoE/DC12V, IK09, DI/DO
E618		3MP Indoor Zoom Dome with D/N, Adaptive IR, Superior WDR, 4.3x Zoom lens, f3.1-13.3mm/F1.4-4.0 (HOV:64.4°-26.4°), P-Iris, Auto Focus (for installation), H.264, 1080p/30fps, 2D+3D DNR, Audio, PoE, IK09, DI/DO
A811		4MP Outdoor Zoom Dome with D/N, IR, Extreme WDR, SLLS, 5x Zoom lens, f2.7-13.5mm/F1.6 (HOV:104°-29°), Auto Focus (for installation), H.265/H.264, 1080p/30fps, , 2D+3D DNR, Audio, PoE/DC12V, IP68, IK10, DI/DO
A817		8MP Video Analytics Outdoor Zoom Dome with D/N, Adaptive IR, Extreme WDR, SLLS, 4.3x Zoom lens, f2.8-12mm/F1.3, Auto Focus (for installation), H.265/H.264, 4K/30fps, 2D+3D DNR, Audio, PoE/DC12V, IP66, IK10, DI/DO, Built-in Analytics
A820		4MP Outdoor Zoom Dome with D/N, IR, Extreme WDR, SLLS, 5x Zoom lens, f2.7-13.5mm/F1.6 (HOV:102.8°-32.4°), H.265/H.264, 3D DNR, Audio, PoE/DC12V, IP68, IK10, DI/DO
A821		6MP Outdoor Zoom Dome with D/N, IR, Extreme WDR, SLLS, 5x Zoom lens, f2.7-13.5mm/F1.6 (HOV:102.1°-34.5°), H.265/H.264, 3D DNR, Audio, PoE/DC12V, IP68, IK10, DI/DO
A85		2MP Video Analytics Outdoor Zoom Dome with D/N, Adaptive IR, Extreme WDR, ELLS, 4.3x Zoom lens, f2.8-12mm/F1.4-2.8, Auto Focus (for installation), H.265/H.264, 1080p/30fps, 2D+3D DNR, Audio, PoE/DC12V, IP66, IK10, DI/DO, Built-in Analytics

A86		5MP Outdoor Zoom Dome with D/N, Adaptive IR, Extreme WDR, SLLS, 5x Zoom lens, f2.7-13.5mm, Auto Focus (for installation), H.265/H.264, 1080p/30fps, 2D+3D DNR, Audio, PoE/DC12V, IP66, IK10, DI/DO
E815		5MP Outdoor Zoom Dome with D/N, Adaptive IR, Basic WDR, 4.3x Zoom lens, f3.1-13.3mm/F1.4-4.0 (HOV:64.74°-25.8°), P-Iris, Auto Focus (for installation), H.264, 1080p/30fps, 2D+3D DNR, Audio, PoE, IP67, IK10, DI/DO
E816		10MP Outdoor Zoom Dome with D/N, Adaptive IR, Basic WDR, 4.3x Zoom lens, f3.1-13.3mm/F1.4-4.0 (HOV:90.6°-34.3°), P-Iris, Auto Focus (for installation), H.264, 1080p/30fps, 2D+3D DNR, Audio, PoE, IP67, IK10, DI/DO

Hemispheric & Fisheye - Hemispheric Dome

B511A		12MP Video Analytics Indoor Hemispheric Dome with D/N, Adaptive IR, Extreme WDR, SLLS, Fixed lens, f1.65mm/F2.8 (HOV:198.5° (overview area), 121.1° (high detail area)), H.264, Dewarping, 2D+3D DNR, Built-in Microphone, PoE/DC12V, DI/DO, Built-in Analytics
B57		6MP Video Analytics Indoor Hemispheric Dome with D/N, Adaptive IR, Extreme WDR, SLLS, Fixed lens, f1.3mm/F2.6 (HOV:187°), H.264, Dewarping, 2D+3D DNR, Audio, PoE/DC12V, DI/DO, Built-in Analytics
B76A		12MP Video Analytics Outdoor Hemispheric Dome with D/N, Adaptive IR, Extreme WDR, SLLS, Fixed lens, f1.65mm/F2.8 (HOV:198.5° (overview area), 121.1° (high detail area)), H.264, Dewarping, 2D+3D DNR, Built-in Microphone, PoE/DC12V, IP68, IK10, DI/DO, Built-in Analytics

Multi-Imager - 2-Sensor 180° Bullet

Q450		8MP Multi-Imager Panoramic Bullet with D/N, Adaptive IR, Superior WDR, SLLS, 2 Fixed lenses, f2.8mm (HOV:180°), H.265/H.264, Dewarping

Multi-Imager - 4-Sensor 180° Dome

Q75		20MP Outdoor Multi-Imager Panoramic Dome with D/N, Adaptive IR, Advanced WDR, SLLS, 4 Fixed lenses, f5.5mm/F1.8 (HOV:180°), H.265/H.264, Audio, High PoE/DC24V/AC24V, IP66, IK10, DI/DO

PTZ - PTZ

B923		3MP Video Analytics Indoor Speed Dome with D/N, Extreme WDR, SLLS, 30x Zoom lens, f4.5-135mm/F1.6-4.4 (HOV:58.5°-3.2°), DC iris, Auto Focus, H.265/H.264, 2D+3D DNR, Audio, High PoE/DC12V, IK09, DI/DO, Built-in Analytics
B934		2MP Video Analytics Indoor Speed Dome with D/N, Extreme WDR, SLLS, 30x Zoom lens, f4.5-135mm/F1.6-4.4 (HOV:62.4°-3.5°), DC iris, Auto Focus, H.264, 1080p/60fps, 2D+3D DNR, Audio, High PoE/DC 12V, IK09, DI/DO, Built-in Analytics
B911		3MP Video Analytics Outdoor Mini PTZ with D/N, Extreme WDR, SLLS, 10x Zoom lens, f4.7-47mm/F1.6-3.0 (HOV:58°-5.8°), DC iris, Auto Focus, H.265/H.264, 2D+3D DNR, Audio, PoE/DC12V, IP67, IK10, DI/DO, Built-in Analytics
B912		5MP Video Analytics Outdoor Mini PTZ with D/N, Extreme WDR, SLLS, 10x Zoom lens, f4.7-47mm/F1.6-3.0 (HOV:50.67°-5.14°), DC iris, Auto Focus, H.265/H.264, 2D+3D DNR, Audio, PoE/DC12V, IP67, IK10, DI/DO, Built-in Analytics
B915		3MP Video Analytics Outdoor Speed Dome with D/N, Adaptive IR, Extreme WDR, SLLS, 36x Zoom lens, f4.6-165.6mm/F1.55-5.0 (HOV:57.6°-2.35°) , DC iris, Auto Focus, H.265/H.264, 2D+3D DNR, Audio, High PoE/AC24V, IP66, IK10 (metal casing), DI/DO, Built-in Analytics

B916		2MP Video Analytics Outdoor Speed Dome with D/N, Extreme WDR, SLLS, 20x Zoom lens, f4.7-94mm/F1.6-3.5 (HOV:62°-2.8°), DC iris, Auto Focus, H.264, 1080p/60fps, 2D+3D DNR, Audio, MicroSDHC/MicroSDXC, High PoE/AC24V, IP67, IK10, DI/DO, Built-in Analytics
B928		5MP Video Analytics Outdoor Speed Dome with D/N, Adaptive IR, Extreme WDR, SLLS, 36x Zoom lens, f4.6-165.6mm/F1.55-5.0 (HOV:51.14°-2.17°), DC iris, Auto Focus, H.265/H.264, 2D+3D DNR, Audio, High PoE/AC24V, IP66, IK10 (metal casing), DI/DO, Built-in Analytics
I915		2MP Video Analytics Outdoor Speed Dome with D/N, Adaptive IR, Extreme WDR, ELLS, 36x Zoom lens, f4.6-165.6mm/F1.55-5.0 (HOV:62.7°-2.7°), DC iris, Auto Focus, H.264, 1080p/60fps, 2D+3D DNR, Audio, High PoE/AC24V, IP66, IK10 (metal casing), DI/DO, Built-in Analytics
I98		2MP Video Analytics Outdoor Speed Dome with D/N, Adaptive IR, Extreme WDR, SLLS, 33x Zoom lens, f4.5-148.5mm/F1.6-5.0 (HOV:69.3°-3°), DC iris, Auto Focus, H.264, 1080p/60fps, 2D+3D DNR, Audio, High PoE/AC24V, IP66, IK10 (metal casing), DI/DO, Built-in Analytics
Z952		4MP Outdoor Speed Dome with D/N, Adaptive IR, Superior WDR, SLLS, 25x Zoom lens, f4.8-120mm/F1.5-3.8 (HOV: 52.20°-2.74°), Auto Focus, H.265/H.264, 1080p/30fps, 2D+3D DNR, Audio, High PoE/DC12V, IP66, IK10, DI/DO
Z954		8MP Outdoor Speed Dome with D/N, Adaptive IR, Superior WDR, SLLS, 25x Zoom lens, f6-150mm/F1.5-3.4 (HOV: 60.5°-3.1°), Auto Focus, H.265/H.264, 4K/30fps, 2D+3D DNR, Audio, High PoE/DC24V/AC24V, IP66, DI/DO
Z956		4MP Outdoor Speed Dome with D/N, Extreme WDR, SLLS, 33x Zoom lens, f4.5-148.5mm/F1.5-4.0 (HOV: 51.4°-2.5°), Auto Focus, H.265, 3D DNR, Audio, High PoE/DC24V/AC24V, IP67, IK10, DI/DO, RS-485
Z957		4MP Outdoor Speed Dome with D/N, Adaptive IR, Extreme WDR, ELLS, 33x Zoom lens, f4.5-148.5mm/F1.5-4.0 (HOV: 51.4°-2.5°), Auto Focus, H.265/H.264, 2D+3D DNR, Audio, High PoE/DC24V/AC24V, IP66, IK10, DI/DO, RS-485

Covert - Covert

Q113		2MP Indoor L-Shape Pinhole Covert with Basic WDR, SLLS, Fixed lens, f3.7mm/F2.5 (HOV:84.5°), H.264, 1080p/30fps, 2D+3D DNR, Audio, PoE/DC12V, EN50155, DI/DO, RS-232
Q115		5MP Indoor L-Shape Pinhole Covert with Basic WDR, Fixed lens, f3.7mm/F2.5 (HOV:70.2°), H.264, DNR, Audio, PoE/DC12V, EN50155, DI/DO, RS-232
Q12		2MP Indoor Covert with Basic WDR, SLLS, Fixed lens, f2.55mm/F2.2 (HOV:110.3°), H.264, 1080p/30fps, 2D+3D DNR, Audio, PoE/DC12V, EN50155, DI/DO, RS-232

Video Encoder - Video Encoder

V21		1-Channel 960H/D1 H.264 Video Encoder with, BNC Video Input, RJ-45 Video Output, Audio, MicroSDHC/MicroSDXC, RS-485, RS-422, DI/DO, PoE/DC12V
V24		4-Channel 960H/D1 H.264 Extended Temperature Video Encoder with, BNC Video Input, RJ-45 Video Output, Audio, MicroSDHC/MicroSDXC, RS-485, RS-422, DI/DO, PoE/DC12V

Video Encoder - Rackmount Video Encoder

V32		16-Channel 960H/D1 H.264 Rackmount Video Encoder with, BNC Video Input, RJ-45 Video Output, Audio, MicroSDHC/MicroSDXC, RS-485, RS-422, DI/DO, AC100-240V

Power Supply Accessories - Power Adapter

PPBX-0011		Power Adapter AC 100~240V, with universal connectors for all DC12V powered devices

2026/11/25

- For product and mounting accessory information, visit: www.acti.com/products and www.acti.com/mountingselector
- All specifications are subject to change without notice.