R71CF-36



2MP Mifare LCD Card Face Recognition Wiegand Reader and Controller with Bundle 6,000 Card Database / 5,000 Face Database.

Specifications

Product Profile

Product Type	Reader and Controller
Device Type	Access Controller RFID Reader Face Reader
Product Application	Access Control with Card + Face Recognition (99%) , Intercom Station
Maximum Resolution	2MP
Description	2MP Mifare LCD Card Face Recognition Wiegand Reader and Controller with Bundle 6,000 Card Database / 5,000 Face Database.
LCD Screen	7" Color Touch Screen; Resolution: 1024 x 600

Lens

Number of Lenses	2 Lenses
Focal Length	Fixed focal

Video

Built-in Analytics	Face Recognition, RFID Recognition

Audio

Audio Type	2-way, Built-in Microphone, Built-in Speaker

Network

Ethernet Port	1 x Ethernet (10/100/1000 Base-T), RJ-45 connector

Video Analytics

Analysis Source Type	Video, Image
Metadata Accuracy	Excellent
Face Recognition Distance	0.3m - 3m

Event

Event Log	50,000

System

Operating System	Linux

Access Control Functionality

Access Mode	Card only, Face only, Card and Face

RFID Card

RFID Frequency	13.56 MHz
RFID Standard	ISO 14443A
RFID Options	Mifare

Storage

User Database	Card Capacity: 6000 Face Picture Capacity: 5000
Card + Face Detection User Limit	5000
Face Only Detection User Limit	5000

Interface

Serial Port	1 x RS-485
Digital Input/Output	2/1

General

Power Source	DC 12V (adapter not included), 3 A
Weight	1158g (2.553lb)
Dimensions	(W x H x D): 239mm x 116.5mm x 33mm (9.41" x 4.59" x 1.30")
Environmental Casing	Weather resistant (IP65)
Operating Temperature	-30°C ~ 60°C (-22°F ~ 140°F)
Operating Humidity	0% - 90% RH, non-condensing
Warranty	1 Year(s). For extended warranty offering, see http://www.acti.com/support/warranty

Related Products

Access Control System - Access Card

PACD-0004		RFID Card Mifare 13.56 MHz

Power Supply Accessories - Power Adapter

PPBX-0016		Power Adapter AC 100~240V (12V/5A Output), with universal connectors for R7 series

2026/9/17