

R71CF-35



2MP Mifare LCD Card Face Recognition Wiegand Reader and Controller with Bundle 50,000 Card Database / 20,000 Face Database.

Specifications

Product Profile

Product Type	Reader and Controller
Device Type	Access Controller RFID Reader Face Reader
Product Application	Access Control with Card + Face Recognition (99%) , Intercom Station
Maximum Resolution	2MP
Description	2MP Mifare LCD Card Face Recognition Wiegand Reader and Controller with Bundle 50,000 Card Database / 20,000 Face Database.
LCD Screen	7" Color Touch Screen; Resolution: 1024 x 600

Lens

Number of Lenses	2 Lenses
Focal Length	Fixed focal

Video

Built-in Analytics	Face Recognition, RFID Recognition
--------------------	------------------------------------

Audio

Audio Type	2-way, Built-in Microphone, Built-in Speaker
------------	--

Network

Ethernet Port	1 x Ethernet (10/100/1000 Base-T), RJ-45 connector
---------------	--

Video Analytics

Analysis Source Type	Video, Image
Metadata Accuracy	Excellent
Face Recognition Distance	0.3m - 3m

Event

Event Log	100,000
-----------	---------

System

Operating System	Linux
------------------	-------

Access Control Functionality

Access Mode	Card only, Face only, Card and Face
-------------	-------------------------------------

RFID Card

RFID Frequency	13.56 MHz
RFID Standard	ISO 14443A
RFID Options	Mifare

Storage

User Database	Card Capacity: 50000 Face Picture Capacity: 20000
Card + Face Detection User Limit	20,000
Face Only Detection User Limit	20,000

Interface

Serial Port	1 x RS-485
Digital Input/Output	2/1

General

Power Source	DC 12V (adapter not included), 3 A
Dimensions	(W x H x D): 239mm x 116.5mm x 33mm (9.41" x 4.59" x 1.30")
Environmental Casing	Weather resistant (IP65)
Operating Temperature	-30°C ~ 60°C (-22°F ~ 140°F)
Operating Humidity	0% - 90% RH, non-condensing
Warranty	1 Year(s). For extended warranty offering, see http://www.acti.com/support/warranty

Related Products

Access Control System - Access Card

PACD-0004	 RFID Card Mifare 13.56 MHz
-----------	--

Power Supply Accessories - Power Adapter

PPBX-0016



Power Adapter AC 100~240V (12V/5A Output), with universal connectors for R7 series