PMAX-0103



Straight Tube with Bracket

Specifications

Product Profile

Product Type	Camera Mount
Application Environment	Indoor/Outdoor
Description	Straight Tube with Bracket

General

Weight	609.5g (1.34lb)
Dimensions	(W x H x D): 140mm x 134mm x 309mm (5.52" x 5.28" x 12.17")
Color	Warm Gray
Material	Aluminum
Warranty	1 Year(s)

Related Products

Dome - Zoom Dome

A810		5MP Outdoor Zoom Dome with D/N, Adaptive IR, Extreme WDR, SLLS, 5x Zoom lens, f2.7-13.5mm/F1.4-3.3 (HOV:96.8°-30.7°), Adaptive iris, Auto Focus (for installation), H.265/H.264, 1080p/30fps, 2D+3D DNR, Audio, PoE/DC12V, IP66, IK10, DI/DO

A811		4MP Outdoor Zoom Dome with D/N, IR, Extreme WDR, SLLS, 5x Zoom lens, f2.7-13.5mm/F1.6 (HOV:104°-29°), Auto Focus (for installation), H.265/H.264, 1080p/30fps, , 2D+3D DNR, Audio, PoE/DC12V, IP68, IK10, DI/DO
A817		8MP Video Analytics Outdoor Zoom Dome with D/N, Adaptive IR, Extreme WDR, SLLS, 4.3x Zoom lens, f2.8-12mm/F1.3, Auto Focus (for installation), H.265/H.264, 4K/30fps, 2D+3D DNR, Audio, PoE/DC12V, IP66, IK10, DI/DO, Built-in Analytics
A820		4MP Outdoor Zoom Dome with D/N, IR, Extreme WDR, SLLS, 5x Zoom lens, f2.7-13.5mm/F1.6 (HOV:102.8°-32.4°), H.265/H.264, 3D DNR, Audio, PoE/DC12V, IP68, IK10, DI/DO
A821		6MP Outdoor Zoom Dome with D/N, IR, Extreme WDR, SLLS, 5x Zoom lens, f2.7-13.5mm/F1.6 (HOV:102.1°-34.5°), H.265/H.264, 3D DNR, Audio, PoE/DC12V, IP68, IK10, DI/DO
A822		
A826		5MP Outdoor Zoom Dome with D/N, Adaptive IR, Extreme WDR, SLLS, 4.4x Zoom lens, f2.7-12mm/F1.6 (HOV:102.1°-31.5°), P-Iris, Auto Focus, H.265/H.264, 1080p/30fps, 2D+3D DNR, Audio, PoE/DC12V/AC24V, IP66, IK10, DI/DO
A828		
Z810		8MP Outdoor Zoom Dome with D/N, Adaptive IR, Superior WDR, SLLS, 4.3x Zoom lens, f2.8-12mm/F1.6 (HOV:99.8°-31.1°), Auto Focus (for installation), H.265/H.264, 1440p/30fps, 2D+3D DNR, Built-in Microphone, PoE/DC12V, IP67, IK10 (metal casing), DI/DO
Z818		8MP Deep Learning AI 5x Outdoor Zoom Dome with IR LED 40m, White LED 40m, Smart Dual Light, ColorVizion, WDR 120dB

Hemispheric & Fisheye - Hemispheric Dome

A711		12MP Outdoor Hemispheric Dome with D/N, Adaptive IR, Extreme WDR, SLLS, Fixed lens, f1.65mm/F2.8 (HOV:180°), H.265/H.264, Dewarping, 2D+3D DNR, Built-in Microphone, PoE/DC12V, IP66, IK10, DI/DO
A713		5MP Outdoor Hemispheric Dome with D/N, Adaptive IR, Superior WDR, SLLS, Fixed lens, f1.1mm/F2.4, H.265/H.264, Dewarping, 2D+3D DNR, Audio, PoE/DC12V, IP66, IK10, DI/DO

PTZ - PTZ

B915		3MP Video Analytics Outdoor Speed Dome with D/N, Adaptive IR, Extreme WDR, SLLS, 36x Zoom lens, f4.6-165.6mm/F1.55-5.0 (HOV:57.6°-2.35°) , DC iris, Auto Focus, H.265/H.264, 2D+3D DNR, Audio, High PoE/AC24V, IP66, IK10 (metal casing), DI/DO, Built-in Analytics
B916		2MP Video Analytics Outdoor Speed Dome with D/N, Extreme WDR, SLLS, 20x Zoom lens, f4.7-94mm/F1.6-3.5 (HOV:62°-2.8°), DC iris, Auto Focus, H.264, 1080p/60fps, 2D+3D DNR, Audio, MicroSDHC/MicroSDXC, High PoE/AC24V, IP67, IK10, DI/DO, Built-in Analytics
B928		5MP Video Analytics Outdoor Speed Dome with D/N, Adaptive IR, Extreme WDR, SLLS, 36x Zoom lens, f4.6-165.6mm/F1.55-5.0 (HOV:51.14°-2.17°), DC iris, Auto Focus, H.265/H.264, 2D+3D DNR, Audio, High PoE/AC24V, IP66, IK10 (metal casing), DI/DO, Built-in Analytics
I915		2MP Video Analytics Outdoor Speed Dome with D/N, Adaptive IR, Extreme WDR, ELLS, 36x Zoom lens, f4.6-165.6mm/F1.55-5.0 (HOV:62.7°-2.7°), DC iris, Auto Focus, H.264, 1080p/60fps, 2D+3D DNR, Audio, High PoE/AC24V, IP66, IK10 (metal casing), DI/DO, Built-in Analytics

I98		2MP Video Analytics Outdoor Speed Dome with D/N, Adaptive IR, Extreme WDR, SLLS, 33x Zoom lens, f4.5-148.5mm/F1.6-5.0 (HOV:69.3°-3°), DC iris, Auto Focus, H.264, 1080p/60fps, 2D+3D DNR, Audio, High PoE/AC24V, IP66, IK10 (metal casing), DI/DO, Built-in Analytics
I98-K1		2MP 33x Ant-Corrosion Outdoor Speed Dome with IR LED 200m, WDR 145dB

2026/9/17