PMAX-0123



Extension Tube (for A71, A74, A77, A88, A9x)

Specifications

Product Profile

Product Type	Camera Mount
Application Environment	Indoor/Outdoor
Description	Extension Tube (for A71, A74, A77, A88, A9x)

General

Weight	330g (0.73lb)
Dimensions	(Ø x L): 32mm x 609.6mm (1.26" x 24")
Color	White
Material	Aluminum
Warranty	1 Year(s)

Related Products

Dome - Fixed Dome

E93		5MP Indoor Mini Dome with Basic WDR, Fixed lens, f1.9mm/F2.8 (HOV:126.9° (overview area), 77.4° (high detail area)), H.264, 1080p/30fps, DNR, PoE, IK08

A76		4MP Outdoor Dome with D/N, IR, Extreme WDR, SLLS, Fixed lens, f2.8mm/F1.6 (HOV:99°), H.265/H.264, 3D DNR, Audio, PoE/DC12V, IP68, IK10, DI/DO
A77		6MP Outdoor Dome with D/N, IR, Extreme WDR, SLLS, Fixed lens, f2.8mm/F1.6, H.265/H.264, 3D DNR, Audio, PoE/DC12V, IP67, IK10, DI/DO
A78		
E918		3MP Outdoor Mini Dome with Superior WDR, Fixed lens, f1.9mm/F2.8 (HOV:126.4° (overview area), 77.1° (high detail area)), H.264, 1080p/30fps, DNR, Audio, PoE, IP68, IK10, EN50155
E936		2MP Video Analytics Outdoor Mini Dome with Extreme WDR, SLLS, Fixed lens, f2.55mm/F2.2 (HOV:110.3°), H.264, 1080p/60fps, 2D+3D DNR, Audio, PoE, IP68, IK10, EN50155, Built-in Analytics
Z910		2MP Outdoor Mini Dome with D/N, Adaptive IR, Superior WDR, SLLS, Fixed lens, f2.8mm/F2.0 (HOV:108.6°), H.265/H.264, 1080p/30fps, 2D+3D DNR, PoE/DC12V, IP68, IK10
Z911		4MP Outdoor Mini Dome with D/N, Adaptive IR, Superior WDR, SLLS, Fixed lens, f2.8mm/F2.0 (HOV:90°), H.265/H.264, 1520p/25fps, 2D+3D DNR, PoE/DC12V, IP68, IK10
Z912		5MP Outdoor Mini Dome with D/N, Adaptive IR, Superior WDR, SLLS, Fixed lens, f2.8mm/F1.6 (HOV:112.9°), H.265/H.264, 2D+3D DNR, Built-in Microphone, PoE/DC12V, IP67, IK10
Z913		8MP Deep Learning AI LightGuard f2.8mm Outdoor Fixed Dome with IR LED 50m, WDR 130dB

Hemispheric & Fisheye - Fisheye Dome

E96		

2026/9/17