PMAX-0126



Straight Tube with Bracket and Converter Ring (for Q75)

Specifications

Product Profile

Product Type	Camera Mount
Description	Straight Tube with Bracket and Converter Ring (for Q75)

General

Weight	650g (1.433lb)
Color	Warm Gray
Warranty	1 Year(s)

Related Products

Multi-Imager - 4-Sensor 180° Dome

Q75		20MP Outdoor Multi-Imager Panoramic Dome with D/N, Adaptive IR, Advanced WDR, SLLS, 4 Fixed lenses, f5.5mm/F1.8 (HOV:180°), H.265/H.264, Audio, High PoE/DC24V/AC24V, IP66, IK10, DI/DO

PTZ - PTZ

K953		5MP Deep Learning AI ColorGuard LightGuard 33x Outdoor PTZ with IR LED 250m, ColorVizion, WDR 145dB

K953-2MP		
K958		
Z952		4MP Outdoor Speed Dome with D/N, Adaptive IR, Superior WDR, SLLS, 25x Zoom lens, f4.8-120mm/F1.5-3.8 (HOV: 52.20°-2.74°), Auto Focus, H.265/H.264, 1080p/30fps, 2D+3D DNR, Audio, High PoE/DC12V, IP66, IK10, DI/DO
Z954		8MP Outdoor Speed Dome with D/N, Adaptive IR, Superior WDR, SLLS, 25x Zoom lens, f6-150mm/F1.5-3.4 (HOV: 60.5°-3.1°), Auto Focus, H.265/H.264, 4K/30fps, 2D+3D DNR, Audio, High PoE/DC24V/AC24V, IP66, DI/DO
Z956		4MP Outdoor Speed Dome with D/N, Extreme WDR, SLLS, 33x Zoom lens, f4.5-148.5mm/F1.5-4.0 (HOV: 51.4°-2.5°), Auto Focus, H.265, 3D DNR, Audio, High PoE/DC24V/AC24V, IP67, IK10, DI/DO, RS-485
Z957		4MP Outdoor Speed Dome with D/N, Adaptive IR, Extreme WDR, ELLS, 33x Zoom lens, f4.5-148.5mm/F1.5-4.0 (HOV: 51.4°-2.5°), Auto Focus, H.265/H.264, 2D+3D DNR, Audio, High PoE/DC24V/AC24V, IP66, IK10, DI/DO, RS-485
Z958		2MP Outdoor Speed Dome with D/N, Adaptive IR, Extreme WDR, ELLS, 16x Zoom lens, f5.0-80mm/F1.7-2.8 (HOV: 51.7°-4.89°), Auto Focus, H.265/H.264, 2D+3D DNR, High PoE/DC12V, IP66, IK10