

PMAX-0210

PoE Stainless Steel Housing with Heater, Fan and Bracket



Specifications

Product Profile

Product Type	Box Camera Housing
Description	PoE Stainless Steel Housing with Heater, Fan and Bracket

General

Power Source	High PoE (IEEE802.3at)
Power Consumption	High PoE: Max. 25.5W (camera and housing with heater and fan on)
Weight	9000g (19.842lb)
Dimensions	(Ø x L): 132mm x 400mm (5.20" x 15.75")
Environmental Casing	Weatherproof (IP68)
Fan	Yes, 40°C / 104°F (fan on), 30°C / 86°F (fan off)
Heater	Yes, 15°C / 59°F (heater on), 24°C / 75.2°F (heater off)
Operating Temperature	-30°C ~ 50°C (-22°F ~ 122°F)
Operating Humidity	0% - 95% RH, non-condensing
Approvals	IP68, NEMA 4X (NEMA 250-2014 Type 4X)
Color	Silver
Material	Stainless Steel 316
Warranty	1 Year(s). For extended warranty offering, see http://www.acti.com/support/warranty

Related Products

Box - Fixed Box

A213		5MP Box with D/N, Extreme WDR, ELLS, Fixed lens, f2.8mm/F2.0, Auto Back Focus, H.265/H.264, 2D+3D DNR, Built-in Microphone, PoE/DC12V, DI/DO, RS-485
A29		2MP Box with D/N, Extreme WDR, ELLS, Fixed lens, f2.8mm/F1.8 (HOV:108.6°), Auto Back Focus, H.265/H.264, 1080p/60fps, 2D+3D DNR, Audio, PoE/DC12V, DI/DO, RS-485
E217		2MP Video Analytics Box with D/N, Extreme WDR, SLLS, Fixed lens, f2.93mm/F2.0 (HOV:101.3°), H.264, 1080p/60fps, 2D+3D DNR, Audio, PoE/DC12V, DI/DO, RS-422/RS-485, Built-in Analytics

Box - Zoom Box

A214		5MP Deep Learning AI 40x Zoom Box with WDR 150dB
B26		3MP Video Analytics Zoom Box with D/N, Extreme WDR, SLLS, 36x Zoom lens, f4.6-165.6mm/F1.55-5.0 (HOV:57.6°-2.35°), DC iris, Auto Focus, H.265/H.264, 2D+3D DNR, Audio, PoE/DC12V, DI/DO, RS-422/RS-485, Built-in Analytics

Network & Storage Peripherals - Data Switch

PPSW-0105		PLANET GS-4210-8P2C 8-Port Gigabit 802.3at Managed PoE Switch (PoE Budget 120W)
-----------	---	---