

PMAX-0303

Gooseneck



Specifications

Product Profile

Product Type	Camera Mount
Application Environment	Indoor/Outdoor
Description	Gooseneck

General

Weight	494.5g (1.09lb)
Dimensions	(W x H x D): 145mm x 90mm x 233mm (5.7" x 3.5" x 9.2")
Color	Warm Gray
Material	Aluminum
Warranty	1 Year(s)

Related Products

Dome - Zoom Dome

A811		4MP Outdoor Zoom Dome with D/N, IR, Extreme WDR, SLLS, 5x Zoom lens, f2.7-13.5mm/F1.6 (HOV:104°-29°), Auto Focus (for installation), H.265/H.264, 1080p/30fps, , 2D+3D DNR, Audio, PoE/DC12V, IP68, IK10, DI/DO
------	---	---

A820		4MP Outdoor Zoom Dome with D/N, IR, Extreme WDR, SLLS, 5x Zoom lens, f2.7-13.5mm/F1.6 (HOV:102.8°-32.4°), H.265/H.264, 3D DNR, Audio, PoE/DC12V, IP68, IK10, DI/DO
A821		6MP Outdoor Zoom Dome with D/N, IR, Extreme WDR, SLLS, 5x Zoom lens, f2.7-13.5mm/F1.6 (HOV:102.1°-34.5°), H.265/H.264, 3D DNR, Audio, PoE/DC12V, IP68, IK10, DI/DO
A822		
A826		5MP Outdoor Zoom Dome with D/N, Adaptive IR, Extreme WDR, SLLS, 4.4x Zoom lens, f2.7-12mm/F1.6 (HOV:102.1°-31.5°), P-Iris, Auto Focus, H.265/H.264, 1080p/30fps, 2D+3D DNR, Audio, PoE/DC12V/AC24V, IP66, IK10, DI/DO
A828		

Hemispheric & Fisheye - Hemispheric Dome

A711		12MP Outdoor Hemispheric Dome with D/N, Adaptive IR, Extreme WDR, SLLS, Fixed lens, f1.65mm/F2.8 (HOV:180°), H.265/H.264, Dewarping, 2D+3D DNR, Built-in Microphone, PoE/DC12V, IP66, IK10, DI/DO
A713		5MP Outdoor Hemispheric Dome with D/N, Adaptive IR, Superior WDR, SLLS, Fixed lens, f1.1mm/F2.4, H.265/H.264, Dewarping, 2D+3D DNR, Audio, PoE/DC12V, IP66, IK10, DI/DO

PTZ - PTZ

B915		3MP Video Analytics Outdoor Speed Dome with D/N, Adaptive IR, Extreme WDR, SLLS, 36x Zoom lens, f4.6-165.6mm/F1.55-5.0 (HOV:57.6°-2.35°), DC iris, Auto Focus, H.265/H.264, 2D+3D DNR, Audio, High PoE/AC24V, IP66, IK10 (metal casing), DI/DO, Built-in Analytics
B916		2MP Video Analytics Outdoor Speed Dome with D/N, Extreme WDR, SLLS, 20x Zoom lens, f4.7-94mm/F1.6-3.5 (HOV:62°-2.8°), DC iris, Auto Focus, H.264, 1080p/60fps, 2D+3D DNR, Audio, MicroSDHC/MicroSDXC, High PoE/AC24V, IP67, IK10, DI/DO, Built-in Analytics
B928		5MP Video Analytics Outdoor Speed Dome with D/N, Adaptive IR, Extreme WDR, SLLS, 36x Zoom lens, f4.6-165.6mm/F1.55-5.0 (HOV:51.14°-2.17°), DC iris, Auto Focus, H.265/H.264, 2D+3D DNR, Audio, High PoE/AC24V, IP66, IK10 (metal casing), DI/DO, Built-in Analytics
I915		2MP Video Analytics Outdoor Speed Dome with D/N, Adaptive IR, Extreme WDR, SLLS, 36x Zoom lens, f4.6-165.6mm/F1.55-5.0 (HOV:62.7°-2.7°), DC iris, Auto Focus, H.264, 1080p/60fps, 2D+3D DNR, Audio, High PoE/AC24V, IP66, IK10 (metal casing), DI/DO, Built-in Analytics
I98		2MP Video Analytics Outdoor Speed Dome with D/N, Adaptive IR, Extreme WDR, SLLS, 33x Zoom lens, f4.5-148.5mm/F1.6-5.0 (HOV:69.3°-3°), DC iris, Auto Focus, H.264, 1080p/60fps, 2D+3D DNR, Audio, High PoE/AC24V, IP66, IK10 (metal casing), DI/DO, Built-in Analytics
I98-K1		2MP 33x Ant-Corrosion Outdoor Speed Dome with IR LED 200m, WDR 145dB