

PMAX-0316



Wall Mount (for D5x, D9x, E5x, E9x, E9xx/M)

► Specifications

Product Profile


Product Type	Camera Mount
Application Environment	Indoor
Description	Wall Mount (for D5x, D9x, E5x, E9x, E9xx/M)





General

Weight	278.5g (0.61lb)
Dimensions	(W x H x D): 140.5mm x 121mm x 55.5mm (5.53" x 4.76" x 2.19")
Color	Warm Gray
Material	Aluminum
Warranty	1 Year(s)


► Related Products

Dome - Fixed Dome

E93		5MP Indoor Mini Dome with Basic WDR, Fixed lens, f1.9mm/F2.8 (HOV:126.9° (overview area), 77.4° (high detail area)), H.264, 1080p/30fps, DNR, PoE, IK08
-----	---	---

E918		3MP Outdoor Mini Dome with Superior WDR, Fixed lens, f1.9mm/F2.8 (HOV:126.4° (overview area), 77.1° (high detail area)), H.264, 1080p/30fps, DNR, Audio, PoE, IP68, IK10, EN50155
E933		2MP Video Analytics Outdoor Mini Dome with D/N, Adaptive IR, Extreme WDR, SLLS, Fixed lens, f2.55mm/F2.2 (HOV:110.3°), H.264, 1080p/60fps, 2D+3D DNR, Audio, PoE, IP68, IK10, EN50155, Built-in Analytics
E933M		2MP Video Analytics Outdoor Mini Dome with D/N, Adaptive IR, Extreme WDR, SLLS, M12 connector, Fixed lens, f2.55mm/F2.2 (HOV:110.3°), H.264, 1080p/60fps, 2D+3D DNR, Audio, PoE, IP68, IK10, EN50155, Built-in Analytics
E936		2MP Video Analytics Outdoor Mini Dome with Extreme WDR, SLLS, Fixed lens, f2.55mm/F2.2 (HOV:110.3°), H.264, 1080p/60fps, 2D+3D DNR, Audio, PoE, IP68, IK10, EN50155, Built-in Analytics

Hemispheric & Fisheye - Fisheye Dome

E96		5MP Indoor Mini Fisheye Dome with Basic WDR, Fixed lens, f1.19mm/F2.0 (HOV:189.7° (overview area), 115.7° (high detail area)), H.264, DNR, PoE, IK08
-----	---	--