

PMAX-0344

Gooseneck with Converter Ring (for Q75)



Specifications

Product Profile

Product Type	Camera Mount
Description	Gooseneck with Converter Ring (for Q75)

General

Weight	657g (1.45lb)
Dimensions	(W x H x D): 253mm x 90mm x 301mm (9.96" x 3.55" x 11.85")
Color	Warm Gray
Warranty	1 Year(s)

Related Products

Multi-Imager - 4-Sensor 180° Dome

Q75	 20MP Outdoor Multi-Imager Panoramic Dome with D/N, Adaptive IR, Advanced WDR, SLLS, 4 Fixed lenses, f5.5mm/F1.8 (HOV:180°), H.265/H.264, Audio, High PoE/DC24V/AC24V, IP66, IK10, DI/DO
-----	---

PTZ - PTZ

A952		8MP Outdoor Speed Dome with D/N, IR, Extreme WDR, ELLS, 22x Zoom lens, f6.4-138.5mm/F1.5 (HOV: 62.6°-3.2°), P-Iris, Auto Focus, H.265/H.264, 2D+3D DNR, Audio, High PoE/AC24V, IP66, DI/DO
A955		5MP Deep Learning AI 40x Outdoor Speed Dome with IR LED 250m, WDR 150dB
A956		2MP Outdoor Speed Dome with D/N, IR, Extreme WDR, ELLS, 40x Zoom lens, f4.3-170mm/F1.6 (HOV: 66.1°-1.8°), P-Iris, Auto Focus, H.265/H.264, 2D+3D DNR, Audio, High PoE/AC24V, IP66, DI/DO
A957		
A959		
A981		
A984		
K953		5MP Deep Learning AI ColorGuard LightGuard 33x Outdoor PTZ with IR LED 250m, ColorVizion, WDR 145dB
K953-2MP		
K958		
Z952		4MP Outdoor Speed Dome with D/N, Adaptive IR, Superior WDR, SLLS, 25x Zoom lens, f4.8-120mm/F1.5-3.8 (HOV: 52.20°-2.74°), Auto Focus, H.265/H.264, 1080p/30fps, 2D+3D DNR, Audio, High PoE/DC12V, IP66, IK10, DI/DO
Z954		8MP Outdoor Speed Dome with D/N, Adaptive IR, Superior WDR, SLLS, 25x Zoom lens, f6-150mm/F1.5-3.4 (HOV: 60.5°-3.1°), Auto Focus, H.265/H.264, 4K/30fps, 2D+3D DNR, Audio, High PoE/DC24V/AC24V, IP66, DI/DO
Z956		4MP Outdoor Speed Dome with D/N, Extreme WDR, SLLS, 33x Zoom lens, f4.5-148.5mm/F1.5-4.0 (HOV: 51.4°-2.5°), Auto Focus, H.265, 3D DNR, Audio, High PoE/DC24V/AC24V, IP67, IK10, DI/DO, RS-485
Z957		4MP Outdoor Speed Dome with D/N, Adaptive IR, Extreme WDR, ELLS, 33x Zoom lens, f4.5-148.5mm/F1.5-4.0 (HOV: 51.4°-2.5°), Auto Focus, H.265/H.264, 2D+3D DNR, Audio, High PoE/DC24V/AC24V, IP66, IK10, DI/DO, RS-485
Z958		2MP Outdoor Speed Dome with D/N, Adaptive IR, Extreme WDR, ELLS, 16x Zoom lens, f5.0-80mm/F1.7-2.8 (HOV: 51.7°-4.89°), Auto Focus, H.265/H.264, 2D+3D DNR, High PoE/DC12V, IP66, IK10