

PMAX-0404

Corner Mount (for Z950)



Specifications

Product Profile

Product Type	Camera Mount
Description	Corner Mount (for Z950)

General

Weight	1879g (4.142lb)
Dimensions	(W x H x D): 215mm x 210mm x 122mm (8.5" x 8.3" x 4.8")
Color	White
Material	Aluminum
Warranty	1 Year(s)

Related Products

Multi-Imager - 4-Sensor 360° Dome

Q84		20MP Outdoor Multi-Imager 360 Degree Dome with D/N, IR, four Zoom lenses, f2.7-13.5mm/F1.2 (HOV:110.3°-31°), H.265/H.264, 2D+3D DNR, Built-in Microphone, High PoE/DC24V/AC24V, IP67, IK10, DI/DO
-----	---	---

PTZ - PTZ

K953		5MP Deep Learning AI ColorGuard LightGuard 33x Outdoor PTZ with IR LED 250m, ColorVizion, WDR 145dB
K953-2MP		
K954		5MP Deep Learning AI 42x Outdoor PTZ with IR LED 500m, ColorVizion, WDR 150dB
K958		
Z952		4MP Outdoor Speed Dome with D/N, Adaptive IR, Superior WDR, SLLS, 25x Zoom lens, f4.8-120mm/F1.5-3.8 (HOV: 52.20°-2.74°), Auto Focus, H.265/H.264, 1080p/30fps, 2D+3D DNR, Audio, High PoE/DC12V, IP66, IK10, DI/DO
Z953		8MP Analytics Outdoor Speed Dome with D/N, Adaptive IR, Extreme WDR, SLLS, 40x Zoom lens, f5.7-228mm/F1.2-4.6 (HOV: 61.4°-2.15°), Auto Focus, H.265/H.264, 4K/30fps, 2D+3D DNR, Audio, High PoE/DC24V/AC24V, IP66, DI/DO
Z954		8MP Outdoor Speed Dome with D/N, Adaptive IR, Superior WDR, SLLS, 25x Zoom lens, f6-150mm/F1.5-3.4 (HOV: 60.5°-3.1°), Auto Focus, H.265/H.264, 4K/30fps, 2D+3D DNR, Audio, High PoE/DC24V/AC24V, IP66, DI/DO
Z956		4MP Outdoor Speed Dome with D/N, Extreme WDR, SLLS, 33x Zoom lens, f4.5-148.5mm/F1.5-4.0 (HOV: 51.4°-2.5°), Auto Focus, H.265, 3D DNR, Audio, High PoE/DC24V/AC24V, IP67, IK10, DI/DO, RS-485
Z957		4MP Outdoor Speed Dome with D/N, Adaptive IR, Extreme WDR, ELLS, 33x Zoom lens, f4.5-148.5mm/F1.5-4.0 (HOV: 51.4°-2.5°), Auto Focus, H.265/H.264, 2D+3D DNR, Audio, High PoE/DC24V/AC24V, IP66, IK10, DI/DO, RS-485
Z958		2MP Outdoor Speed Dome with D/N, Adaptive IR, Extreme WDR, ELLS, 16x Zoom lens, f5.0-80mm/F1.7-2.8 (HOV: 51.7°-4.89°), Auto Focus, H.265/H.264, 2D+3D DNR, High PoE/DC12V, IP66, IK10
Z959		4MP Outdoor Speed Dome with D/N, Adaptive IR, Extreme WDR, ELLS, 16x Zoom lens, f5.5-88mm/F1.78-3.73 (HOV: 50.85°-3.47°), Auto Focus, H.265/H.264, 2D+3D DNR, Audio, High PoE/DC12V, IP66, IK10, DI/DO, RS-485