

PMAX-0712

Junction Box (for Z9x, Z714, Z77, K7x)



Specifications

Product Profile

Product Type	Camera Mount
Description	Junction Box (for Z9x, Z714, Z77, K7x)

General

Weight	183.5g (0.405lb)
Dimensions	(Ø x H): 109mm x 36mm (4.3" x 1.4")
Color	White
Material	Aluminum
Warranty	1 Year(s)

Related Products

Dome - Fixed Dome

J71		2MP f2.8mm Outdoor Fixed Dome with IR LED 50m, WDR 130dB
J72		4MP f2.8mm Outdoor Fixed Dome with IR LED 50m, WDR 130dB

J73		5MP Deep Learning AI f2.8mm Outdoor Fixed Dome with IR LED 50m, WDR 130dB
K71		2MP f2.8mm Outdoor Fixed Dome with IR LED 50m, WDR 130dB
K71-P1		2MP f4.0mm Outdoor Fixed Dome with IR LED 50m, WDR 130dB
K72		4MP f2.8mm Outdoor Fixed Dome with IR LED 50m, WDR 130dB
K72-P1		
K73		5MP Deep Learning AI f2.8mm Outdoor Fixed Dome with IR LED 50m, WDR 130dB
Z721		4MP Analytics Outdoor Mini Dome with D/N, Adaptive IR, Extreme WDR, SLLS, M12 connector, Fixed lens, f2.8mm/F1.6 (HOV:101.1°), H.265/H.264, 2D+3D DNR, Audio, DC12V, IP67, IK10
Z91		4MP Outdoor Mini Dome with D/N, Adaptive IR, Extreme WDR, SLLS, Fixed lens, f2.8mm/F2.0 (HOV:101.8°), H.265/H.264, 1080p/30fps, 2D+3D DNR, Audio, PoE/DC12V, IP67, IK10, DI/DO
Z910		2MP Outdoor Mini Dome with D/N, Adaptive IR, Superior WDR, SLLS, Fixed lens, f2.8mm/F2.0 (HOV:108.6°), H.265/H.264, 1080p/30fps, 2D+3D DNR, PoE/DC12V, IP68, IK10
Z911		4MP Outdoor Mini Dome with D/N, Adaptive IR, Superior WDR, SLLS, Fixed lens, f2.8mm/F2.0 (HOV:90°), H.265/H.264, 1520p/25fps, 2D+3D DNR, PoE/DC12V, IP68, IK10
Z912		5MP Outdoor Mini Dome with D/N, Adaptive IR, Superior WDR, SLLS, Fixed lens, f2.8mm/F1.6 (HOV:112.9°), H.265/H.264, 2D+3D DNR, Built-in Microphone, PoE/DC12V, IP67, IK10
Z913		8MP Deep Learning AI LightGuard f2.8mm Outdoor Fixed Dome with IR LED 50m, WDR 130dB