

PMAX-0809

Converter Ring, 1.0" NPT for Third-Party Mounting Accessories



Specifications

Product Profile

Product Type	Camera Mount
Application Environment	Indoor/Outdoor
Description	Converter Ring, 1.0" NPT for Third-Party Mounting Accessories

General

Weight	46.5g (0.103lb)
Dimensions	(Ø x H): 54.1mm x 49mm (2.13" x 1.93")
Color	Warm Gray
Material	Aluminum
Warranty	1 Year(s)

Related Products

Dome - Fixed Dome

E54	 5MP Indoor Dome with D/N, Adaptive IR, Basic WDR, Fixed lens, f3.6mm/F1.8 (HOV:72°), H.264, 1080p/30fps, DNR, PoE
-----	---

E93		5MP Indoor Mini Dome with Basic WDR, Fixed lens, f1.9mm/F2.8 (HOV:126.9° (overview area), 77.4° (high detail area)), H.264, 1080p/30fps, DNR, PoE, IK08
E918		3MP Outdoor Mini Dome with Superior WDR, Fixed lens, f1.9mm/F2.8 (HOV:126.4° (overview area), 77.1° (high detail area)), H.264, 1080p/30fps, DNR, Audio, PoE, IP68, IK10, EN50155
E933		2MP Video Analytics Outdoor Mini Dome with D/N, Adaptive IR, Extreme WDR, SLLS, Fixed lens, f2.55mm/F2.2 (HOV:110.3°), H.264, 1080p/60fps, 2D+3D DNR, Audio, PoE, IP68, IK10, EN50155, Built-in Analytics
E933M		2MP Video Analytics Outdoor Mini Dome with D/N, Adaptive IR, Extreme WDR, SLLS, M12 connector, Fixed lens, f2.55mm/F2.2 (HOV:110.3°), H.264, 1080p/60fps, 2D+3D DNR, Audio, PoE, IP68, IK10, EN50155, Built-in Analytics
E936		2MP Video Analytics Outdoor Mini Dome with Extreme WDR, SLLS, Fixed lens, f2.55mm/F2.2 (HOV:110.3°), H.264, 1080p/60fps, 2D+3D DNR, Audio, PoE, IP68, IK10, EN50155, Built-in Analytics