

PPBX-0011

Power Adapter AC 100~240V, with universal connectors for all DC12V powered devices



Specifications

Product Profile	
Product Type	Power Adapter
Description	Power Adapter AC 100~240V, with universal connectors for all DC12V powered devices
General	
Power Output	DC 12V, 1.5A, Maximum 18W
Power Source	AC 100-240V
Bundled Accessories	Universal power connector
Power Connector Type	United States
Approvals	FCC, UL, PSE
Warranty	1 Year(s)

Related Products

Box - Fixed Box	
A213	 5MP Box with D/N, Extreme WDR, ELLS, Fixed lens, f2.8mm/F2.0, Auto Back Focus, H.265/H.264, 2D+3D DNR, Built-in Microphone, PoE/DC12V, DI/DO, RS-485

A29		2MP Box with D/N, Extreme WDR, ELLS, Fixed lens, f2.8mm/F1.8 (HOV:108.6°), Auto Back Focus, H.265/H.264, 1080p/60fps, 2D+3D DNR, Audio, PoE/DC12V, DI/DO, RS-485
E217		2MP Video Analytics Box with D/N, Extreme WDR, SLLS, Fixed lens, f2.93mm/F2.0 (HOV:101.3°), H.264, 1080p/60fps, 2D+3D DNR, Audio, PoE/DC12V, DI/DO, RS-422/RS-485, Built-in Analytics
Q22		2MP Outdoor Micro Box with Basic WDR, SLLS, Fixed lens, f2.55mm/F2.2 (HOV:110.3°), H.264, 1080p/30fps, DNR, Built-in Microphone, PoE/DC12V, IP68 (for Lens module and Lens cable), IK10 (metal casing), EN50155, DI/DO, RS-232

Box - Zoom Box

A214		5MP Deep Learning AI 40x Zoom Box with WDR 150dB
B26		3MP Video Analytics Zoom Box with D/N, Extreme WDR, SLLS, 36x Zoom lens, f4.6-165.6mm/F1.55-5.0 (HOV:57.6°-2.35°), DC iris, Auto Focus, H.265/H.264, 2D+3D DNR, Audio, PoE/DC12V, DI/DO, RS-422/RS-485, Built-in Analytics

Bullet - Zoom Bullet

B419		5MP Video Analytics Zoom Bullet with D/N, Adaptive IR, Extreme WDR, SLLS, 10x Zoom lens, f4.7-47mm/F1.6-3.0 (HOV:50.67°-5.14°), DC iris, Auto Focus, H.265/H.264, 2D+3D DNR, Built-in Microphone, High PoE/DC12V, IP67, IK10 (metal casing), DI/DO, Built-in Analytics
I42		2MP Video Analytics Zoom Bullet with D/N, Adaptive IR, Extreme WDR, ELLS, 36x Zoom lens, f4.6-165.6mm/F1.55-5.0 (HOV:62.7°-2.7°), DC iris, Auto Focus, H.264, 1080p/60fps, 2D+3D DNR, Audio, PoE/DC12V, IP67, IK10 (metal casing), DI/DO, Built-in Analytics
I47		4MP Zoom Bullet with D/N, Adaptive IR, Advanced WDR, SLLS, 30x Zoom lens, f4.3-129mm/F1.6-5.0 (HOV:66.4°-2.14°), DC iris, Auto Focus, H.264, 1080p/30fps, 2D+3D DNR, Audio, PoE/DC12V, IP67, IK10 (metal casing), DI/DO

Bullet - Thermal Bullet

A374		4MP Deep Learning AI f3.6mm Thermal Bullet with IR LED 30m, White LED 30m, Smart Dual Light, WDR 120dB
A383		4MP Deep Learning AI f35mm Thermal Bullet with IR LED 100m, WDR 120dB

Dome - Zoom Dome

B64		1.3MP Indoor Zoom Dome with D/N, Adaptive IR, Basic WDR, SLLS, 3x Zoom lens, f3-9mm/F1.2-2.1 (HOV:90.6°-31.8°), DC iris, Auto Focus, H.264, 720p/60fps, DNR, Audio, PoE/DC12V, IK09, DI/DO
A817		8MP Video Analytics Outdoor Zoom Dome with D/N, Adaptive IR, Extreme WDR, SLLS, 4.3x Zoom lens, f2.8-12mm/F1.3, Auto Focus (for installation), H.265/H.264, 4K/30fps, 2D+3D DNR, Audio, PoE/DC12V, IP66, IK10, DI/DO, Built-in Analytics
A826		5MP Outdoor Zoom Dome with D/N, Adaptive IR, Extreme WDR, SLLS, 4.4x Zoom lens, f2.7-12mm/F1.6 (HOV:102.1°-31.5°), P-Iris, Auto Focus, H.265/H.264, 1080p/30fps, 2D+3D DNR, Audio, PoE/DC12V/AC24V, IP66, IK10, DI/DO

Hemispheric & Fisheye - Hemispheric Dome

B57		6MP Video Analytics Indoor Hemispheric Dome with D/N, Adaptive IR, Extreme WDR, SLLS, Fixed lens, f1.3mm/F2.6 (HOV:187°), H.264, Dewarping, 2D+3D DNR, Audio, PoE/DC12V, DI/DO, Built-in Analytics
A711		12MP Outdoor Hemispheric Dome with D/N, Adaptive IR, Extreme WDR, SLLS, Fixed lens, f1.65mm/F2.8 (HOV:180°), H.265/H.264, Dewarping, 2D+3D DNR, Built-in Microphone, PoE/DC12V, IP66, IK10, DI/DO
A713		5MP Outdoor Hemispheric Dome with D/N, Adaptive IR, Superior WDR, SLLS, Fixed lens, f1.1mm/F2.4, H.265/H.264, Dewarping, 2D+3D DNR, Audio, PoE/DC12V, IP66, IK10, DI/DO
B76A		12MP Video Analytics Outdoor Hemispheric Dome with D/N, Adaptive IR, Extreme WDR, SLLS, Fixed lens, f1.65mm/F2.8 (HOV:198.5° (overview area), 121.1° (high detail area)), H.264, Dewarping, 2D+3D DNR, Built-in Microphone, PoE/DC12V, IP68, IK10, DI/DO, Built-in Analytics

PTZ - PTZ

B923		3MP Video Analytics Indoor Speed Dome with D/N, Extreme WDR, SLLS, 30x Zoom lens, f4.5-135mm/F1.6-4.4 (HOV:58.5°-3.2°), DC iris, Auto Focus, H.265/H.264, 2D+3D DNR, Audio, High PoE/DC12V, IK09, DI/DO, Built-in Analytics
B934		2MP Video Analytics Indoor Speed Dome with D/N, Extreme WDR, SLLS, 30x Zoom lens, f4.5-135mm/F1.6-4.4 (HOV:62.4°-3.5°), DC iris, Auto Focus, H.264, 1080p/60fps, 2D+3D DNR, Audio, High PoE/DC 12V, IK09, DI/DO, Built-in Analytics
B911		3MP Video Analytics Outdoor Mini PTZ with D/N, Extreme WDR, SLLS, 10x Zoom lens, f4.7-47mm/F1.6-3.0 (HOV:58°-5.8°), DC iris, Auto Focus, H.265/H.264, 2D+3D DNR, Audio, PoE/DC12V, IP67, IK10, DI/DO, Built-in Analytics
B912		5MP Video Analytics Outdoor Mini PTZ with D/N, Extreme WDR, SLLS, 10x Zoom lens, f4.7-47mm/F1.6-3.0 (HOV:50.67°-5.14°), DC iris, Auto Focus, H.265/H.264, 2D+3D DNR, Audio, PoE/DC12V, IP67, IK10, DI/DO, Built-in Analytics

Covert - Covert

Q113		2MP Indoor L-Shape Pinhole Covert with Basic WDR, SLLS, Fixed lens, f3.7mm/F2.5 (HOV:84.5°), H.264, 1080p/30fps, 2D+3D DNR, Audio, PoE/DC12V, EN50155, DI/DO, RS-232
Q115		5MP Indoor L-Shape Pinhole Covert with Basic WDR, Fixed lens, f3.7mm/F2.5 (HOV:70.2°), H.264, DNR, Audio, PoE/DC12V, EN50155, DI/DO, RS-232
Q12		2MP Indoor Covert with Basic WDR, SLLS, Fixed lens, f2.55mm/F2.2 (HOV:110.3°), H.264, 1080p/30fps, 2D+3D DNR, Audio, PoE/DC12V, EN50155, DI/DO, RS-232

Video Encoder - Video Encoder

V21		1-Channel 960H/D1 H.264 Video Encoder with, BNC Video Input, RJ-45 Video Output, Audio, MicroSDHC/MicroSDXC, RS-485, RS-422, DI/DO, PoE/DC12V
V24		4-Channel 960H/D1 H.264 Extended Temperature Video Encoder with, BNC Video Input, RJ-45 Video Output, Audio, MicroSDHC/MicroSDXC, RS-485, RS-422, DI/DO, PoE/DC12V

Access Control System - Lock

PLOC-0002		Soyal LK-1207A-36 Electric Bolt Lock
PLOC-2002		Soyal AR-0600M + AR-0600MZL Magnet Lock + Bracket
PLOC-3001		Automatic door Electric Bolt lock

Audio Devices - Microphone

PMIC-0100		Active Microphone Omnidirectional for all Cameras with Line-in Audio
-----------	---	--

Illuminators - IR LED Illuminator

PLED-0200		SPINLUX (SL-A2IRXX10-24CL) IR Illuminator 10° Angle with 120 m approx. range
PLED-0201		SPINLUX (SL-A2IRXX25-24CL) IR Illuminator 25° Angle with 50 m approx. range