

PPBX-0015

Power Adapter AC 100~240V (12V/2A Output), with universal connectors for A426, Q450, Q75, VMGB series, R21CF-30, R11C-30, R71CF-31



Specifications

Product Profile

Product Type	Power Adapter
Description	Power Adapter AC 100~240V (12V/2A Output), with universal connectors for A426, Q450, Q75, VMGB series, R21CF-30, R11C-30, R71CF-31

General

Power Output	DC 12V, Maximum 24W
Power Source	AC 100-240V
Power Connector Type	Universal
Warranty	1 Year(s)

Related Products

Bullet - Zoom Bullet

A426	 5MP Zoom Bullet with D/N, Adaptive IR, Extreme WDR, SLLS, 4.4x Zoom lens, f2.7-12mm/F1.6 (HOV:102.1°-31.5°), P-Iris, Auto Focus, H.265/H.264, 2D+3D DNR, Audio, PoE/DC12V/AC24V, IP66, DI/DO
------	--

A427		4MP Face Recognition Zoom Bullet with D/N, Adaptive IR, Extreme WDR, SLLS, 4.3x Zoom lens, f2.8-12mm/F1.2-2.5 (HOV:114.5°-41.8°), P-Iris, Auto Focus, H.265/H.264, 2D+3D DNR, High PoE/DC12V, IP67, IK10 (metal casing), DI/DO
------	---	--

Bullet - Thermal Bullet

VMGB-370		4MP Metadata Camera with Day/Night, IR LED, Built-in Human Temperature Detection
----------	---	--

Multi-Imager - 2-Sensor 180° Bullet

Q450		8MP Multi-Imager Panoramic Bullet with D/N, Adaptive IR, Superior WDR, SLLS, 2 Fixed lenses, f2.8mm (HOV:180°), H.265/H.264, Dewarping
------	---	--

Multi-Imager - 4-Sensor 180° Dome

Q75		20MP Outdoor Multi-Imager Panoramic Dome with D/N, Adaptive IR, Advanced WDR, SLLS, 4 Fixed lenses, f5.5mm/F1.8 (HOV:180°), H.265/H.264, Audio, High PoE/DC24V/AC24V, IP66, IK10, DI/DO
-----	---	---

Access Control System - Reader and Controller

R10C-10		Mifare Card Wiegand Reader with Keypad, DC 10-24V, Wiegand, ABA-II, ASYNC
R11C-30		Dual Band LCD Card Reader and Controller with 16,000 Card Database, Networking, Keypad, DC 10-24V, IP54, DI (Egress x 2, Door Contact x 2), Relay Output, Wiegand, RS-485
R11C-311		Access Controller with 16,000 Card Database
R11C-33		HID LCD Card Reader and Controller with 16,000 Card Database, TCP/IP, Keypad, Keypad, DC 10-24V, IP54, DI (Egress x 2, Door Contact x 2), Relay Output, Wiegand, RS-485
R71CF-31		2MP Mifare LCD Card Face Recognition Wiegand Wireless Reader and Controller with Bundle 5,000 Card Database / 3,000 Face Database, Door Bell Button, Networking, DC12V, IP65, DI x 2, DO x 1, RJ-45, Wiegand, RS-485
R71CF-313		2MP Mifare Face Recognition Reader and Controller (6000 faces), Audio, DC12V, IP65, DI x 2, DO x 1, RJ-45, Wiegand, RS-485

Detectors - Smoke Detector

PDTR-0001		Cigarette Smoke Detector DC 7-12V
-----------	---	-----------------------------------