

R11C-34

RFID Reader and Controller with Bundled
3000 Card Database



Access Controller with HID Module, 3,000 Card Database

► Specifications

Product Profile

Product Type	Reader and Controller
Device Type	Access Controller RFID Reader
Product Application	RFID Card Detection
Description	Access Controller with HID Module, 3,000 Card Database

Video

Built-in Analytics	RFID Recognition
--------------------	------------------

Video Analytics

Analysis Source Type	Text
Metadata Accuracy	Excellent

Event

Event Log	3000
-----------	------

Access Control Functionality

Access Mode	Card only, Card or Password, Card and Password
-------------	--

RFID Card

RFID Frequency	125 KHz, 13.56 MHz
----------------	--------------------

Reading Range	[125 kHz] 3-7cm
RFID Options	EM, Mifare, NFC, HID Prox

Storage

User Database	Card Capacity: 3000
---------------	---------------------

Interface

Button	Illuminated touch-panel keypad
Serial Port	1 x RS-485, 9600 bps (N,8,1)
Digital Input	Egress x 1, Door contact x 1
Relay Output	Door lock x 1, Alarm relay x 1
External Reader	Wiegand Input x 1
Indicator	Outside Bi-Color LED Frame, LED x 3, Buzzer x 1

General

Power Source	DC 9-24V (adapter not included)
Power Consumption	3 W (DC)
Weight	120g (0.26lb)
Dimensions	(W x H x D): 81mm x 118mm x 33.2mm (3.19" x 4.65" x 1.31")
Environmental Casing	Weather resistant (IP65)
Operating Temperature	-20°C ~ 65°C (-4°F ~ 149°F)
Operating Humidity	20% - 90% RH, non-condensing
Color	Black
Material	Base Plate: Plastic (PC)
Warranty	1 Year(s). For extended warranty offering, see http://www.acti.com/support/warranty