

PPOE-0104



High PoE injector Single-port, 60W Gigabit Midspan, 4-Pairs, 802.3at Compliant, AC 100~240V, with universal connectors (for I93~I910, I915, B915~B917, B922, B928, B945, B949, A950, A951, A952, A956)

Specifications

Product Profile

Product Type	PoE Injector
Description	High PoE injector Single-port, 60W Gigabit Midspan, 4-Pairs, 802.3at Compliant, AC 100~240V, with universal connectors (for I93~I910, I915, B915~B917, B922, B928, B945, B949, A950, A951, A952, A956)

Network

Ethernet Port	(DATA & POWER OUT) PoE: 1 port(s), Ethernet (10/100/1000 Base-T), RJ-45 connector (DATA IN) 1 x RJ-45 connector Network Cable: 4-pair UTP Category 5/53/6, 2-pair UTP Category 3/4/5, up to 100m (328ft)
---------------	--

General

PoE Standard	IEEE 802.3at
PoE Output	Maximum 60 Watts (4-pair) Maximum 30 Watts (2-pair)
Power Output	DC 56V
Power Source	AC 100-240V
Weight	246g (0.54lb)
Dimensions	(W x H x D): 115mm x 31mm x 62.5mm (4.53" x 1.22" x 2.46")
Operating Temperature	0°C ~ 50°C (32°F ~ 122°F)
Warranty	1 Year(s)

Related Products

PTZ - PTZ

B915		3MP Video Analytics Outdoor Speed Dome with D/N, Adaptive IR, Extreme WDR, SLLS, 36x Zoom lens, f4.6-165.6mm/F1.55-5.0 (HOV:57.6°-2.35°), DC iris, Auto Focus, H.265/H.264, 2D+3D DNR, Audio, High PoE/AC24V, IP66, IK10 (metal casing), DI/DO, Built-in Analytics
B916		2MP Video Analytics Outdoor Speed Dome with D/N, Extreme WDR, SLLS, 20x Zoom lens, f4.7-94mm/F1.6-3.5 (HOV:62°-2.8°), DC iris, Auto Focus, H.264, 1080p/60fps, 2D+3D DNR, Audio, MicroSDHC/MicroSDXC, High PoE/AC24V, IP67, IK10, DI/DO, Built-in Analytics
B928		5MP Video Analytics Outdoor Speed Dome with D/N, Adaptive IR, Extreme WDR, SLLS, 36x Zoom lens, f4.6-165.6mm/F1.55-5.0 (HOV:51.14°-2.17°), DC iris, Auto Focus, H.265/H.264, 2D+3D DNR, Audio, High PoE/AC24V, IP66, IK10 (metal casing), DI/DO, Built-in Analytics
I915		2MP Video Analytics Outdoor Speed Dome with D/N, Adaptive IR, Extreme WDR, ELLS, 36x Zoom lens, f4.6-165.6mm/F1.55-5.0 (HOV:62.7°-2.7°), DC iris, Auto Focus, H.264, 1080p/60fps, 2D+3D DNR, Audio, High PoE/AC24V, IP66, IK10 (metal casing), DI/DO, Built-in Analytics
I98		2MP Video Analytics Outdoor Speed Dome with D/N, Adaptive IR, Extreme WDR, SLLS, 33x Zoom lens, f4.5-148.5mm/F1.6-5.0 (HOV:69.3°-3°), DC iris, Auto Focus, H.264, 1080p/60fps, 2D+3D DNR, Audio, High PoE/AC24V, IP66, IK10 (metal casing), DI/DO, Built-in Analytics