

PLED-0200



IR Illuminator 10° Angle , with 120 m approx. range

► Specifications

Product Profile

Original Manufacturer	Spinlux
Product Type	IR LED Illuminator
Original Model	SL-A2IRXX10-24CL
Description	IR Illuminator 10° Angle , with 120 m approx. range
IR Working Distance	120m




General

Wavelength	850 nm
Illuminating Angle	10°
Power Source	DC 12V
Weight	940.5g (2.073lb)
Dimensions	(W x H x D): 105mm x 54mm x 154mm (4.1" x 2.1" x 6")
Environmental Casing	Weatherproof (IP66), Vandal proof (IK10)
Operating Temperature	-50°C ~ 50°C (-58°F ~ 122°F)
Approvals	CE, FCC, VCCI, C-Tick, IP66, IK10
Color	Black
Material	Plastic Aluminum


Warranty	1 Year(s)
----------	-----------

▶ Related Products


Box - Fixed Box

A213		5MP Box with D/N, Extreme WDR, ELLS, Fixed lens, f2.8mm/F2.0, Auto Back Focus, H.265/H.264, 2D+3D DNR, Built-in Microphone, PoE/DC12V, DI/DO, RS-485
A29		2MP Box with D/N, Extreme WDR, ELLS, Fixed lens, f2.8mm/F1.8 (HOV:108.6°), Auto Back Focus, H.265/H.264, 1080p/60fps, 2D+3D DNR, Audio, PoE/DC12V, DI/DO, RS-485
E217		2MP Video Analytics Box with D/N, Extreme WDR, SLLS, Fixed lens, f2.93mm/F2.0 (HOV:101.3°), H.264, 1080p/60fps, 2D+3D DNR, Audio, PoE/DC12V, DI/DO, RS-422/RS-485, Built-in Analytics




Bullet - Fixed Bullet

E33A		5MP Bullet with D/N, Adaptive IR, Basic WDR, Fixed lens, f4.2mm/F1.8 (HOV:62.7°), H.264, 1080p/30fps, DNR, PoE, IP68, IK10 (metal casing)
------	---	---




Bullet - Vari-focal Bullet

E43B		5MP Bullet with D/N, Adaptive IR, Basic WDR, Vari-focal lens, f2.8-12mm/F1.4 (HOV:69.2°-28.2°), H.264, 1080p/30fps, DNR, Audio, PoE, IP68, IK10 (metal casing), DI/DO
------	---	---





Bullet - Zoom Bullet

B419		5MP Video Analytics Zoom Bullet with D/N, Adaptive IR, Extreme WDR, SLLS, 10x Zoom lens, f4.7-47mm/F1.6-3.0 (HOV:50.67°-5.14°), DC iris, Auto Focus, H.265/H.264, 2D+3D DNR, Built-in Microphone, High PoE/DC12V, IP67, IK10 (metal casing), DI/DO, Built-in Analytics
I42		2MP Video Analytics Zoom Bullet with D/N, Adaptive IR, Extreme WDR, ELLS, 36x Zoom lens, f4.6-165.6mm/F1.55-5.0 (HOV:62.7°-2.7°), DC iris, Auto Focus, H.264, 1080p/60fps, 2D+3D DNR, Audio, PoE/DC12V, IP67, IK10 (metal casing), DI/DO, Built-in Analytics
I47		4MP Zoom Bullet with D/N, Adaptive IR, Advanced WDR, SLLS, 30x Zoom lens, f4.3-129mm/F1.6-5.0 (HOV:66.4°-2.14°), DC iris, Auto Focus, H.264, 1080p/30fps, 2D+3D DNR, Audio, PoE/DC12V, IP67, IK10 (metal casing), DI/DO



Dome - Fixed Dome

E54		5MP Indoor Dome with D/N, Adaptive IR, Basic WDR, Fixed lens, f3.6mm/F1.8 (HOV:72°), H.264, 1080p/30fps, DNR, PoE
E933		2MP Video Analytics Outdoor Mini Dome with D/N, Adaptive IR, Extreme WDR, SLLS, Fixed lens, f2.55mm/F2.2 (HOV:110.3°), H.264, 1080p/60fps, 2D+3D DNR, Audio, PoE, IP68, IK10, EN50155, Built-in Analytics
E933M		2MP Video Analytics Outdoor Mini Dome with D/N, Adaptive IR, Extreme WDR, SLLS, M12 connector, Fixed lens, f2.55mm/F2.2 (HOV:110.3°), H.264, 1080p/60fps, 2D+3D DNR, Audio, PoE, IP68, IK10, EN50155, Built-in Analytics








Dome - Zoom Dome



B64		1.3MP Indoor Zoom Dome with D/N, Adaptive IR, Basic WDR, SLLS, 3x Zoom lens, f3-9mm/F1.2-2.1 (HOV:90.6°-31.8°), DC iris, Auto Focus, H.264, 720p/60fps, DNR, Audio, PoE/DC12V, IK09, DI/DO
E618		3MP Indoor Zoom Dome with D/N, Adaptive IR, Superior WDR, 4.3x Zoom lens, f3.1-13.3mm/F1.4-4.0 (HOV:64.4°-26.4°), P-Iris, Auto Focus (for installation), H.264, 1080p/30fps, 2D+3D DNR, Audio, PoE, IK09, DI/DO
E815		5MP Outdoor Zoom Dome with D/N, Adaptive IR, Basic WDR, 4.3x Zoom lens, f3.1-13.3mm/F1.4-4.0 (HOV:64.74°-25.8°), P-Iris, Auto Focus (for installation), H.264, 1080p/30fps, 2D+3D DNR, Audio, PoE, IP67, IK10, DI/DO
E816		10MP Outdoor Zoom Dome with D/N, Adaptive IR, Basic WDR, 4.3x Zoom lens, f3.1-13.3mm/F1.4-4.0 (HOV:90.6°-34.3°), P-Iris, Auto Focus (for installation), H.264, 1080p/30fps, 2D+3D DNR, Audio, PoE, IP67, IK10, DI/DO

Hemispheric & Fisheye - Hemispheric Dome


B511A		12MP Video Analytics Indoor Hemispheric Dome with D/N, Adaptive IR, Extreme WDR, SLLS, Fixed lens, f1.65mm/F2.8 (HOV:198.5° (overview area), 121.1° (high detail area)), H.264, Dewarping, 2D+3D DNR, Built-in Microphone, PoE/DC12V, DI/DO, Built-in Analytics
B76A		12MP Video Analytics Outdoor Hemispheric Dome with D/N, Adaptive IR, Extreme WDR, SLLS, Fixed lens, f1.65mm/F2.8 (HOV:198.5° (overview area), 121.1° (high detail area)), H.264, Dewarping, 2D+3D DNR, Built-in Microphone, PoE/DC12V, IP68, IK10, DI/DO, Built-in Analytics

PTZ - PTZ

B923		3MP Video Analytics Indoor Speed Dome with D/N, Extreme WDR, SLLS, 30x Zoom lens, f4.5-135mm/F1.6-4.4 (HOV:58.5°-3.2°), DC iris, Auto Focus, H.265/H.264, 2D+3D DNR, Audio, High PoE/DC12V, IK09, DI/DO, Built-in Analytics
B934		2MP Video Analytics Indoor Speed Dome with D/N, Extreme WDR, SLLS, 30x Zoom lens, f4.5-135mm/F1.6-4.4 (HOV:62.4°-3.5°), DC iris, Auto Focus, H.264, 1080p/60fps, 2D+3D DNR, Audio, High PoE/DC 12V, IK09, DI/DO, Built-in Analytics
B911		3MP Video Analytics Outdoor Mini PTZ with D/N, Extreme WDR, SLLS, 10x Zoom lens, f4.7-47mm/F1.6-3.0 (HOV:58°-5.8°), DC iris, Auto Focus, H.265/H.264, 2D+3D DNR, Audio, PoE/DC12V, IP67, IK10, DI/DO, Built-in Analytics
B912		5MP Video Analytics Outdoor Mini PTZ with D/N, Extreme WDR, SLLS, 10x Zoom lens, f4.7-47mm/F1.6-3.0 (HOV:50.67°-5.14°), DC iris, Auto Focus, H.265/H.264, 2D+3D DNR, Audio, PoE/DC12V, IP67, IK10, DI/DO, Built-in Analytics
B915		3MP Video Analytics Outdoor Speed Dome with D/N, Adaptive IR, Extreme WDR, SLLS, 36x Zoom lens, f4.6-165.6mm/F1.55-5.0 (HOV:57.6°-2.35°), DC iris, Auto Focus, H.265/H.264, 2D+3D DNR, Audio, High PoE/AC24V, IP66, IK10 (metal casing), DI/DO, Built-in Analytics
B916		2MP Video Analytics Outdoor Speed Dome with D/N, Extreme WDR, SLLS, 20x Zoom lens, f4.7-94mm/F1.6-3.5 (HOV:62°-2.8°), DC iris, Auto Focus, H.264, 1080p/60fps, 2D+3D DNR, Audio, MicroSDHC/MicroSDXC, High PoE/AC24V, IP67, IK10, DI/DO, Built-in Analytics
B928		5MP Video Analytics Outdoor Speed Dome with D/N, Adaptive IR, Extreme WDR, SLLS, 36x Zoom lens, f4.6-165.6mm/F1.55-5.0 (HOV:51.14°-2.17°), DC iris, Auto Focus, H.265/H.264, 2D+3D DNR, Audio, High PoE/AC24V, IP66, IK10 (metal casing), DI/DO, Built-in Analytics

I915		2MP Video Analytics Outdoor Speed Dome with D/N, Adaptive IR, Extreme WDR, ELLS, 36x Zoom lens, f4.6-165.6mm/F1.55-5.0 (HOV:62.7°-2.7°), DC iris, Auto Focus, H.264, 1080p/60fps, 2D+3D DNR, Audio, High PoE/AC24V, IP66, IK10 (metal casing), DI/DO, Built-in Analytics
I98		2MP Video Analytics Outdoor Speed Dome with D/N, Adaptive IR, Extreme WDR, SLLS, 33x Zoom lens, f4.5-148.5mm/F1.6-5.0 (HOV:69.3°-3°), DC iris, Auto Focus, H.264, 1080p/60fps, 2D+3D DNR, Audio, High PoE/AC24V, IP66, IK10 (metal casing), DI/DO, Built-in Analytics

Power Supply Accessories - Power Adapter

PPBX-0011		Power Adapter AC 100~240V, with universal connectors for all DC12V powered devices
-----------	---	--