

PMMC-0301

Memory Card (SDSDQQ-064G-G46A)



Specifications

Product Profile

Original Manufacturer	SanDisk
Product Type	Memory Card
Original Model	64G MicroSDXC Class 10 (SDSDQQ-064G-G46A)
Description	Memory Card (SDSDQQ-064G-G46A)

General

Capacity	64 GB
Read/Write Speed	up to 20 MB/s
Weight	8g (0.018lb)
Dimensions	(W x H x D): 15mm x 1mm x 11mm (0.59" x 0.04" x 0.43")
Warranty	1 Year(s)
Card Type	microSDXC

Related Products

Cube - Fixed Cube

C11W		1.3MP Wireless Cube with Basic WDR, Fixed lens, f3.6mm/F1.8 (HOV:55°), H.264, 720p/30fps, 2D+3D DNR, Built-in Microphone, DC12V
E11A		1MP Cube with Basic WDR, Fixed lens, f4.2mm/F1.8 (HOV:53.8°), H.264, 720p/30fps, DNR, Built-in Microphone, PoE
E13A		5MP Cube with Basic WDR, Fixed lens, f2.8mm/F2.0 (HOV:92.6°), H.264, 1080p/30fps, DNR, Built-in Microphone, PoE
E14		10MP Cube with Basic WDR, Fixed lens, f3.6mm/F1.8 (HOV:99°), H.264, 1080p/30fps, DNR, Built-in Microphone, PoE
E19		5MP Cube with Extreme WDR, SLLS, Fixed lens, f2.8mm/F1.8 (HOV:117.5°), H.265/H.264, 1080p/30fps, 2D+3D DNR, Built-in Microphone, PoE

Box - Fixed Box

A213		5MP Box with D/N, Extreme WDR, ELLS, Fixed lens, f2.8mm/F2.0, Auto Back Focus, H.265/H.264, 2D+3D DNR, Built-in Microphone, PoE/DC12V, DI/DO, RS-485
A29		2MP Box with D/N, Extreme WDR, ELLS, Fixed lens, f2.8mm/F1.8 (HOV:108.6°), Auto Back Focus, H.265/H.264, 1080p/60fps, 2D+3D DNR, Audio, PoE/DC12V, DI/DO, RS-485
Q22		2MP Outdoor Micro Box with Basic WDR, SLLS, Fixed lens, f2.55mm/F2.2 (HOV:110.3°), H.264, 1080p/30fps, DNR, Built-in Microphone, PoE/DC12V, IP68 (for Lens module and Lens cable), IK10 (metal casing), EN50155, DI/DO, RS-232

Box - Zoom Box

B26		3MP Video Analytics Zoom Box with D/N, Extreme WDR, SLLS, 36x Zoom lens, f4.6-165.6mm/F1.55-5.0 (HOV:57.6°-2.35°), DC iris, Auto Focus, H.265/H.264, 2D+3D DNR, Audio, PoE/DC12V, DI/DO, RS-422/RS-485, Built-in Analytics
-----	---	--

Bullet - Fixed Bullet

E33A		5MP Bullet with D/N, Adaptive IR, Basic WDR, Fixed lens, f4.2mm/F1.8 (HOV:62.7°), H.264, 1080p/30fps, DNR, PoE, IP68, IK10 (metal casing)
------	---	---

Bullet - Vari-focal Bullet

E43B		5MP Bullet with D/N, Adaptive IR, Basic WDR, Vari-focal lens, f2.8-12mm/F1.4 (HOV:69.2°-28.2°), H.264, 1080p/30fps, DNR, Audio, PoE, IP68, IK10 (metal casing), DI/DO
------	---	---

Bullet - Zoom Bullet

B419		5MP Video Analytics Zoom Bullet with D/N, Adaptive IR, Extreme WDR, SLLS, 10x Zoom lens, f4.7-47mm/F1.6-3.0 (HOV:50.67°-5.14°), DC iris, Auto Focus, H.265/H.264, 2D+3D DNR, Built-in Microphone, High PoE/DC12V, IP67, IK10 (metal casing), DI/DO, Built-in Analytics
------	---	--

I42		2MP Video Analytics Zoom Bullet with D/N, Adaptive IR, Extreme WDR, ELLS, 36x Zoom lens, f4.6-165.6mm/F1.55-5.0 (HOV:62.7°-2.7°), DC iris, Auto Focus, H.264, 1080p/60fps, 2D+3D DNR, Audio, PoE/DC12V, IP67, IK10 (metal casing), DI/DO, Built-in Analytics
I47		4MP Zoom Bullet with D/N, Adaptive IR, Advanced WDR, SLLS, 30x Zoom lens, f4.3-129mm/F1.6-5.0 (HOV:66.4°-2.14°), DC iris, Auto Focus, H.264, 1080p/30fps, 2D+3D DNR, Audio, PoE/DC12V, IP67, IK10 (metal casing), DI/DO
Z411		4MP Zoom Bullet with D/N, Adaptive IR, Extreme WDR, ELLS, 22x Zoom lens, f6.5-143mm/F1.5 HOV:61.3°-3.4°, DC iris, Auto Focus (for installation), H.265/H.264, 2D+3D DNR, Audio, PoE/AC24V, IP67, DI/DO, RS-485

Dome - Fixed Dome

E93		5MP Indoor Mini Dome with Basic WDR, Fixed lens, f1.9mm/F2.8 (HOV:126.9° (overview area), 77.4° (high detail area)), H.264, 1080p/30fps, DNR, PoE, IK08
E933		2MP Video Analytics Outdoor Mini Dome with D/N, Adaptive IR, Extreme WDR, SLLS, Fixed lens, f2.55mm/F2.2 (HOV:110.3°), H.264, 1080p/60fps, 2D+3D DNR, Audio, PoE, IP68, IK10, EN50155, Built-in Analytics
E933M		2MP Video Analytics Outdoor Mini Dome with D/N, Adaptive IR, Extreme WDR, SLLS, M12 connector, Fixed lens, f2.55mm/F2.2 (HOV:110.3°), H.264, 1080p/60fps, 2D+3D DNR, Audio, PoE, IP68, IK10, EN50155, Built-in Analytics
E936		2MP Video Analytics Outdoor Mini Dome with Extreme WDR, SLLS, Fixed lens, f2.55mm/F2.2 (HOV:110.3°), H.264, 1080p/60fps, 2D+3D DNR, Audio, PoE, IP68, IK10, EN50155, Built-in Analytics

Dome - Zoom Dome

B64		1.3MP Indoor Zoom Dome with D/N, Adaptive IR, Basic WDR, SLLS, 3x Zoom lens, f3-9mm/F1.2-2.1 (HOV:90.6°-31.8°), DC iris, Auto Focus, H.264, 720p/60fps, DNR, Audio, PoE/DC12V, IK09, DI/DO
E618		3MP Indoor Zoom Dome with D/N, Adaptive IR, Superior WDR, 4.3x Zoom lens, f3.1-13.3mm/F1.4-4.0 (HOV:64.4°-26.4°), P-Iris, Auto Focus (for installation), H.264, 1080p/30fps, 2D+3D DNR, Audio, PoE, IK09, DI/DO
E815		5MP Outdoor Zoom Dome with D/N, Adaptive IR, Basic WDR, 4.3x Zoom lens, f3.1-13.3mm/F1.4-4.0 (HOV:64.74°-25.8°), P-Iris, Auto Focus (for installation), H.264, 1080p/30fps, 2D+3D DNR, Audio, PoE, IP67, IK10, DI/DO
E816		10MP Outdoor Zoom Dome with D/N, Adaptive IR, Basic WDR, 4.3x Zoom lens, f3.1-13.3mm/F1.4-4.0 (HOV:90.6°-34.3°), P-Iris, Auto Focus (for installation), H.264, 1080p/30fps, 2D+3D DNR, Audio, PoE, IP67, IK10, DI/DO

Hemispheric & Fisheye - Hemispheric Dome

B511A		12MP Video Analytics Indoor Hemispheric Dome with D/N, Adaptive IR, Extreme WDR, SLLS, Fixed lens, f1.65mm/F2.8 (HOV:198.5° (overview area), 121.1° (high detail area)), H.264, Dewarping, 2D+3D DNR, Built-in Microphone, PoE/DC12V, DI/DO, Built-in Analytics
B57		6MP Video Analytics Indoor Hemispheric Dome with D/N, Adaptive IR, Extreme WDR, SLLS, Fixed lens, f1.3mm/F2.6 (HOV:187°), H.264, Dewarping, 2D+3D DNR, Audio, PoE/DC12V, DI/DO, Built-in Analytics
A711		12MP Outdoor Hemispheric Dome with D/N, Adaptive IR, Extreme WDR, SLLS, Fixed lens, f1.65mm/F2.8 (HOV:180°), H.265/H.264, Dewarping, 2D+3D DNR, Built-in Microphone, PoE/DC12V, IP66, IK10, DI/DO
A713		5MP Outdoor Hemispheric Dome with D/N, Adaptive IR, Superior WDR, SLLS, Fixed lens, f1.1mm/F2.4, H.265/H.264, Dewarping, 2D+3D DNR, Audio, PoE/DC12V, IP66, IK10, DI/DO

B76A		12MP Video Analytics Outdoor Hemispheric Dome with D/N, Adaptive IR, Extreme WDR, SLLS, Fixed lens, f1.65mm/F2.8 (HOV:198.5° (overview area), 121.1° (high detail area)), H.264, Dewarping, 2D+3D DNR, Built-in Microphone, PoE/DC12V, IP68, IK10, DI/DO, Built-in Analytics
------	---	--

Hemispheric & Fisheye - Fisheye Cube

E16		10MP Fisheye Cube with Basic WDR, Fixed lens, f1.37mm/F2.0 (HOV:187.7° (overview area), 114.5° (high detail area)), H.264, DNR, Built-in Microphone, PoE
-----	---	--

Hemispheric & Fisheye - Fisheye Dome

E96		
-----	---	--

PTZ - PTZ

B923		3MP Video Analytics Indoor Speed Dome with D/N, Extreme WDR, SLLS, 30x Zoom lens, f4.5-135mm/F1.6-4.4 (HOV:58.5°-3.2°), DC iris, Auto Focus, H.265/H.264, 2D+3D DNR, Audio, High PoE/DC12V, IK09, DI/DO, Built-in Analytics
B934		2MP Video Analytics Indoor Speed Dome with D/N, Extreme WDR, SLLS, 30x Zoom lens, f4.5-135mm/F1.6-4.4 (HOV:62.4°-3.5°), DC iris, Auto Focus, H.264, 1080p/60fps, 2D+3D DNR, Audio, High PoE/DC 12V, IK09, DI/DO, Built-in Analytics
B911		3MP Video Analytics Outdoor Mini PTZ with D/N, Extreme WDR, SLLS, 10x Zoom lens, f4.7-47mm/F1.6-3.0 (HOV:58°-5.8°), DC iris, Auto Focus, H.265/H.264, 2D+3D DNR, Audio, PoE/DC12V, IP67, IK10, DI/DO, Built-in Analytics
B912		5MP Video Analytics Outdoor Mini PTZ with D/N, Extreme WDR, SLLS, 10x Zoom lens, f4.7-47mm/F1.6-3.0 (HOV:50.67°-5.14°), DC iris, Auto Focus, H.265/H.264, 2D+3D DNR, Audio, PoE/DC12V, IP67, IK10, DI/DO, Built-in Analytics
B915		3MP Video Analytics Outdoor Speed Dome with D/N, Adaptive IR, Extreme WDR, SLLS, 36x Zoom lens, f4.6-165.6mm/F1.55-5.0 (HOV:57.6°-2.35°), DC iris, Auto Focus, H.265/H.264, 2D+3D DNR, Audio, High PoE/AC24V, IP66, IK10 (metal casing), DI/DO, Built-in Analytics
B916		2MP Video Analytics Outdoor Speed Dome with D/N, Extreme WDR, SLLS, 20x Zoom lens, f4.7-94mm/F1.6-3.5 (HOV:62°-2.8°), DC iris, Auto Focus, H.264, 1080p/60fps, 2D+3D DNR, Audio, MicroSDHC/MicroSDXC, High PoE/AC24V, IP67, IK10, DI/DO, Built-in Analytics
B928		5MP Video Analytics Outdoor Speed Dome with D/N, Adaptive IR, Extreme WDR, SLLS, 36x Zoom lens, f4.6-165.6mm/F1.55-5.0 (HOV:51.14°-2.17°), DC iris, Auto Focus, H.265/H.264, 2D+3D DNR, Audio, High PoE/AC24V, IP66, IK10 (metal casing), DI/DO, Built-in Analytics
I915		2MP Video Analytics Outdoor Speed Dome with D/N, Adaptive IR, Extreme WDR, SLLS, 36x Zoom lens, f4.6-165.6mm/F1.55-5.0 (HOV:62.7°-2.7°), DC iris, Auto Focus, H.264, 1080p/60fps, 2D+3D DNR, Audio, High PoE/AC24V, IP66, IK10 (metal casing), DI/DO, Built-in Analytics
I98		2MP Video Analytics Outdoor Speed Dome with D/N, Adaptive IR, Extreme WDR, SLLS, 33x Zoom lens, f4.5-148.5mm/F1.6-5.0 (HOV:69.3°-3°), DC iris, Auto Focus, H.264, 1080p/60fps, 2D+3D DNR, Audio, High PoE/AC24V, IP66, IK10 (metal casing), DI/DO, Built-in Analytics

Covert - Covert

Q113		2MP Indoor L-Shape Pinhole Covert with Basic WDR, SLLS, Fixed lens, f3.7mm/F2.5 (HOV:84.5°), H.264, 1080p/30fps, 2D+3D DNR, Audio, PoE/DC12V, EN50155, DI/DO, RS-232
------	---	--

Q115		5MP Indoor L-Shape Pinhole Covert with Basic WDR, Fixed lens, f3.7mm/F2.5 (HOV:70.2°), H.264, DNR, Audio, PoE/DC12V, EN50155, DI/DO, RS-232
------	---	---

Access & Communication - Door Station

Q950		6MP Outdoor Door Station with D/N, IR, Extreme WDR, SLLS, Fixed lens, f1.65mm/F2.8 (HOV:198.5° (overview area), 121.1° (high detail area)), RFID, PIR, Push Button, H.264, Dewarping, 2D+3D DNR, Built-in Microphone, Speaker, PoE/DC12V, IP66, IK09, DI/DO, RS-422/RS-485
------	---	--

Video Decoder - Video Decoder

ECD-200		16-Channel Megapixel H.265 Video Decoder with RJ-45 Video Input, HDMI Video Output, Wireless (Optional), Audio, DI/DO, MicroSDHC/MicroSDXC card slot, USB 3.0, DC12V
---------	---	--