PPOC-0100



Power over Coax Adapter Kit

Specifications

Product Profile

Original Manufacturer	PLANET
Product Type	PoE over Coaxial Extender Kit
Original Model	LRP-101C-KIT
Description	Power over Coax Adapter Kit

General

PoE Power Budget	Maximum 25 W
Weight	420g (0.926lb)
Dimensions	(W x H x D): 140mm x 52mm x 194mm (5.512" x 2.047" x 7.638")
Operating Temperature	-20°C ~ 70°C (-4°F ~ 158°F)
Approvals	CE, FCC
Warranty	1 Year(s)

Related Products

Cube - Fixed Cube

C11W		1.3MP Wireless Cube with Basic WDR, Fixed lens, f3.6mm/F1.8 (HOV:55°), H.264, 720p/30fps, 2D+3D DNR, Built-in Microphone, DC12V
E11		1MP Cube with Basic WDR, Fixed lens, f4.2mm/F1.8 (HOV:53.8°), H.264, 720p/30fps, DNR, Audio, PoE
E11A		1MP Cube with Basic WDR, Fixed lens, f4.2mm/F1.8 (HOV:53.8°), H.264, 720p/30fps, DNR, Built-in Microphone, PoE
E13A		5MP Cube with Basic WDR, Fixed lens, f2.8mm/F2.0 (HOV:92.6°), H.264, 1080p/30fps, DNR, Built-in Microphone, PoE
E14		10MP Cube with Basic WDR, Fixed lens, f3.6mm/F1.8 (HOV:99°), H.264, 1080p/30fps, DNR, Built-in Microphone, PoE

Box - Fixed Box

E217		2MP Video Analytics Box with D/N, Extreme WDR, SLLS, Fixed lens, f2.93mm/F2.0 (HOV:101.3°), H.264, 1080p/60fps, 2D+3D DNR, Audio, PoE/DC12V, DI/DO, RS-422/RS-485, Built-in Analytics
Q22		2MP Outdoor Micro Box with Basic WDR, SLLS, Fixed lens, f2.55mm/F2.2 (HOV:110.3°), H.264, 1080p/30fps, DNR, Built-in Microphone, PoE/DC12V, IP68 (for Lens module and Lens cable), IK10 (metal casing), EN50155, DI/DO, RS-232

Box - Zoom Box

B26		3MP Video Analytics Zoom Box with D/N, Extreme WDR, SLLS, 36x Zoom lens, f4.6-165.6mm/F1.55-5.0 (HOV:57.6°-2.35°), DC iris, Auto Focus, H.265/H.264, 2D+3D DNR, Audio, PoE/DC12V, DI/DO, RS-422/RS-485, Built-in Analytics

Bullet - Fixed Bullet

E33A		5MP Bullet with D/N, Adaptive IR, Basic WDR, Fixed lens, f4.2mm/F1.8 (HOV:62.7°), H.264, 1080p/30fps, DNR, PoE, IP68, IK10 (metal casing)

Bullet - Vari-focal Bullet

E43B		5MP Bullet with D/N, Adaptive IR, Basic WDR, Vari-focal lens, f2.8-12mm/F1.4 (HOV:69.2°-28.2°), H.264, 1080p/30fps, DNR, Audio, PoE, IP68, IK10 (metal casing), DI/DO

Bullet - Zoom Bullet

B419		5MP Video Analytics Zoom Bullet with D/N, Adaptive IR, Extreme WDR, SLLS, 10x Zoom lens, f4.7-47mm/F1.6-3.0 (HOV:50.67°-5.14°), DC iris, Auto Focus, H.265/H.264, 2D+3D DNR, Built-in Microphone, High PoE/DC12V, IP67, IK10 (metal casing), DI/DO, Built-in Analytics
I42		2MP Video Analytics Zoom Bullet with D/N, Adaptive IR, Extreme WDR, ELLS, 36x Zoom lens, f4.6-165.6mm/F1.55-5.0 (HOV:62.7°-2.7°), DC iris, Auto Focus, H.264, 1080p/60fps, 2D+3D DNR, Audio, PoE/DC12V, IP67, IK10 (metal casing), DI/DO, Built-in Analytics

I47		4MP Zoom Bullet with D/N, Adaptive IR, Advanced WDR, SLLS, 30x Zoom lens, f4.3-129mm/F1.6-5.0 (HOV:66.4°-2.14°), DC iris, Auto Focus, H.264, 1080p/30fps, 2D+3D DNR, Audio, PoE/DC12V, IP67, IK10 (metal casing), DI/DO

Dome - Fixed Dome

E54		5MP Indoor Dome with D/N, Adaptive IR, Basic WDR, Fixed lens, f3.6mm/F1.8 (HOV:72°), H.264, 1080p/30fps, DNR, PoE
E93		5MP Indoor Mini Dome with Basic WDR, Fixed lens, f1.9mm/F2.8 (HOV:126.9° (overview area), 77.4° (high detail area)), H.264, 1080p/30fps, DNR, PoE, IK08
E918		3MP Outdoor Mini Dome with Superior WDR, Fixed lens, f1.9mm/F2.8 (HOV:126.4° (overview area), 77.1° (high detail area)), H.264, 1080p/30fps, DNR, Audio, PoE, IP68, IK10, EN50155
E936		2MP Video Analytics Outdoor Mini Dome with Extreme WDR, SLLS, Fixed lens, f2.55mm/F2.2 (HOV:110.3°), H.264, 1080p/60fps, 2D+3D DNR, Audio, PoE, IP68, IK10, EN50155, Built-in Analytics

Dome - Zoom Dome

B64		1.3MP Indoor Zoom Dome with D/N, Adaptive IR, Basic WDR, SLLS, 3x Zoom lens, f3-9mm/F1.2-2.1 (HOV:90.6°-31.8°), DC iris, Auto Focus, H.264, 720p/60fps, DNR, Audio, PoE/DC12V, IK09, DI/DO
E618		3MP Indoor Zoom Dome with D/N, Adaptive IR, Superior WDR, 4.3x Zoom lens, f3.1-13.3mm/F1.4-4.0 (HOV:64.4°-26.4°), P-Iris, Auto Focus (for installation), H.264, 1080p/30fps, 2D+3D DNR, Audio, PoE, IK09, DI/DO
E815		5MP Outdoor Zoom Dome with D/N, Adaptive IR, Basic WDR, 4.3x Zoom lens, f3.1-13.3mm/F1.4-4.0 (HOV:64.74°-25.8°), P-Iris, Auto Focus (for installation), H.264, 1080p/30fps, 2D+3D DNR, Audio, PoE, IP67, IK10, DI/DO
E816		10MP Outdoor Zoom Dome with D/N, Adaptive IR, Basic WDR, 4.3x Zoom lens, f3.1-13.3mm/F1.4-4.0 (HOV:90.6°-34.3°), P-Iris, Auto Focus (for installation), H.264, 1080p/30fps, 2D+3D DNR, Audio, PoE, IP67, IK10, DI/DO
KCM-7311		4MP Outdoor Dome with D/N, Advanced WDR, SLLS, 3.6x Zoom lens, f3.3-12mm/F1.4-2.9 (HOV:77.2°-22.6°), P-Iris, Auto Focus, H.264, 1080p/15fps, 2D+3D DNR, Audio, PoE/DC12V, IP67, Vandal Proof, DI/DO

Hemispheric & Fisheye - Hemispheric Dome

B511A		12MP Video Analytics Indoor Hemispheric Dome with D/N, Adaptive IR, Extreme WDR, SLLS, Fixed lens, f1.65mm/F2.8 (HOV:198.5° (overview area), 121.1° (high detail area)), H.264, Dewarping, 2D+3D DNR, Built-in Microphone, PoE/DC12V, DI/DO, Built-in Analytics
B57		6MP Video Analytics Indoor Hemispheric Dome with D/N, Adaptive IR, Extreme WDR, SLLS, Fixed lens, f1.3mm/F2.6 (HOV:187°), H.264, Dewarping, 2D+3D DNR, Audio, PoE/DC12V, DI/DO, Built-in Analytics
B76A		12MP Video Analytics Outdoor Hemispheric Dome with D/N, Adaptive IR, Extreme WDR, SLLS, Fixed lens, f1.65mm/F2.8 (HOV:198.5° (overview area), 121.1° (high detail area)), H.264, Dewarping, 2D+3D DNR, Built-in Microphone, PoE/DC12V, IP68, IK10, DI/DO, Built-in Analytics

Hemispheric & Fisheye - Fisheye Cube

E16		10MP Fisheye Cube with Basic WDR, Fixed lens, f1.37mm/F2.0 (HOV:187.7° (overview area), 114.5° (high detail area)), H.264, DNR, Built-in Microphone, PoE

Hemispheric & Fisheye - Fisheye Dome

E96		

PTZ - PTZ

B923		3MP Video Analytics Indoor Speed Dome with D/N, Extreme WDR, SLLS, 30x Zoom lens, f4.5-135mm/F1.6-4.4 (HOV:58.5°-3.2°), DC iris, Auto Focus, H.265/H.264, 2D+3D DNR, Audio, High PoE/DC12V, IK09, DI/DO, Built-in Analytics
B934		2MP Video Analytics Indoor Speed Dome with D/N, Extreme WDR, SLLS, 30x Zoom lens, f4.5-135mm/F1.6-4.4 (HOV:62.4°-3.5°), DC iris, Auto Focus, H.264, 1080p/60fps, 2D+3D DNR, Audio, High PoE/DC 12V, IK09, DI/DO, Built-in Analytics
B911		3MP Video Analytics Outdoor Mini PTZ with D/N, Extreme WDR, SLLS, 10x Zoom lens, f4.7-47mm/F1.6-3.0 (HOV:58°-5.8°), DC iris, Auto Focus, H.265/H.264, 2D+3D DNR, Audio, PoE/DC12V, IP67, IK10, DI/DO, Built-in Analytics
B912		5MP Video Analytics Outdoor Mini PTZ with D/N, Extreme WDR, SLLS, 10x Zoom lens, f4.7-47mm/F1.6-3.0 (HOV:50.67°-5.14°), DC iris, Auto Focus, H.265/H.264, 2D+3D DNR, Audio, PoE/DC12V, IP67, IK10, DI/DO, Built-in Analytics
B915		3MP Video Analytics Outdoor Speed Dome with D/N, Adaptive IR, Extreme WDR, SLLS, 36x Zoom lens, f4.6-165.6mm/F1.55-5.0 (HOV:57.6°-2.35°) , DC iris, Auto Focus, H.265/H.264, 2D+3D DNR, Audio, High PoE/AC24V, IP66, IK10 (metal casing), DI/DO, Built-in Analytics
B916		2MP Video Analytics Outdoor Speed Dome with D/N, Extreme WDR, SLLS, 20x Zoom lens, f4.7-94mm/F1.6-3.5 (HOV:62°-2.8°), DC iris, Auto Focus, H.264, 1080p/60fps, 2D+3D DNR, Audio, MicroSDHC/MicroSDXC, High PoE/AC24V, IP67, IK10, DI/DO, Built-in Analytics
B928		5MP Video Analytics Outdoor Speed Dome with D/N, Adaptive IR, Extreme WDR, SLLS, 36x Zoom lens, f4.6-165.6mm/F1.55-5.0 (HOV:51.14°-2.17°), DC iris, Auto Focus, H.265/H.264, 2D+3D DNR, Audio, High PoE/AC24V, IP66, IK10 (metal casing), DI/DO, Built-in Analytics
I915		2MP Video Analytics Outdoor Speed Dome with D/N, Adaptive IR, Extreme WDR, ELLS, 36x Zoom lens, f4.6-165.6mm/F1.55-5.0 (HOV:62.7°-2.7°), DC iris, Auto Focus, H.264, 1080p/60fps, 2D+3D DNR, Audio, High PoE/AC24V, IP66, IK10 (metal casing), DI/DO, Built-in Analytics
I98		2MP Video Analytics Outdoor Speed Dome with D/N, Adaptive IR, Extreme WDR, SLLS, 33x Zoom lens, f4.5-148.5mm/F1.6-5.0 (HOV:69.3°-3°), DC iris, Auto Focus, H.264, 1080p/60fps, 2D+3D DNR, Audio, High PoE/AC24V, IP66, IK10 (metal casing), DI/DO, Built-in Analytics

Covert - Covert

Q113		2MP Indoor L-Shape Pinhole Covert with Basic WDR, SLLS, Fixed lens, f3.7mm/F2.5 (HOV:84.5°), H.264, 1080p/30fps, 2D+3D DNR, Audio, PoE/DC12V, EN50155, DI/DO, RS-232
Q115		5MP Indoor L-Shape Pinhole Covert with Basic WDR, Fixed lens, f3.7mm/F2.5 (HOV:70.2°), H.264, DNR, Audio, PoE/DC12V, EN50155, DI/DO, RS-232
Q12		2MP Indoor Covert with Basic WDR, SLLS, Fixed lens, f2.55mm/F2.2 (HOV:110.3°), H.264, 1080p/30fps, 2D+3D DNR, Audio, PoE/DC12V, EN50155, DI/DO, RS-232

Access & Communication - Door Station

Q950		6MP Outdoor Door Station with D/N, IR, Extreme WDR, SLLS, Fixed lens, f1.65mm/F2.8 (HOV:198.5° (overview area), 121.1° (high detail area)), RFID, PIR, Push Button, H.264, Dewarping, 2D+3D DNR, Built-in Microphone, Speaker, PoE/DC12V, IP66, IK09, DI/DO, RS-422/RS-485

2026/9/17

• For product and mounting accessory information, visit: www.acti.com/products and www.acti.com/mountingselector
• All specifications are subject to change without notice.