

A371

4MP f3.6mm Thermal Bullet with IR LED 30m, White LED 30m, WDR 120dB



- 4 Megapixel, f3.6mm, Thermal Bullet
- Aperture F1.6, IR LED 30m, Superior WDR (120 dB)
- White LED 30m
- Smart Intrusion Protection
- Weatherproof (IP68), Vandal proof (IK10)
- Overheating Detection, Fire Detection, Thermal Surveillance
- Thermal Resolution 256(H) X 192(V), NETD <40mK
- Fire detection up to 43.2m

Specifications

Product Profile

Product Type	Thermal Bullet
Product Application	Overheating Detection, Fire Detection, Thermal Surveillance
Application Environment	Outdoor
Maximum Resolution	4MP
Image Sensor	Progressive Scan CMOS + Thermal sensor
Sensor Size	Optical: 1/2.7"
Effective Pixels	Thermal: 256(H) X 192(V) Optical: 2688(H) X 1520(V)
Pixel Interval	12 μ m
Spectral Range	8-14 μ m
Thermal Sensitivity	NETD <40mK at F1.0
Spatial Resolution	3.33 mrad
Day / Night	Yes
Low Light Sensitivity	Superior
Minimum Illumination	Color: 0.0089 lux at F1.6 (AGC on); B/W: 0 lux (IR LED on)
Mechanical IR Cut Filter	Yes

IR LED	Adaptive IR LED
IR Working Distance	30m
White LED	Yes
White LED Working Distance	30m
S/N Ratio	75 dB

Lens

Number of Lenses	2 Lenses
Focal Length	Fixed focal, f3.6mm (Thermal camera) Fixed focal, f4.3mm (Visual camera)
Aperture	(Thermal camera) F1.0 (Visual camera) F1.6
Horizontal Viewing Angle	(Thermal camera) 50° (Visual camera) 84°
Vertical Viewing Angle	(Thermal camera) 37.3° (Visual camera) 43.1°

Video

Compression	H.265, H.264, MJPEG
Maximum Frame Rate vs. Resolution	(Visual camera) (60Hz) 30 fps at 2688 x 1520 30 fps at 1920 x 1080 30 fps at 1280 x 720 30 fps at 704 x 480 30 fps at 352 x 240 (50Hz) 25 fps at 2688 x 1520 25 fps at 1920 x 1080 25 fps at 1280 x 720 25 fps at 704 x 576 25 fps at 352 x 288 (Thermal camera) 25 fps at 1280 x 720 25 fps at 704 x 576 25 fps at 640 x 512 25 fps at 320 x 240
Multi-Streaming	Simultaneous dual streams
Digital Noise Reduction	3D DNR
Wide Dynamic Range	Superior WDR (120 dB)
Built-in Analytics	People Detection, Vehicle Detection, Smart Intrusion Protection (, People Line Crossing Detection, People Intrusion Detection, People Enter Area Detection, People Exit Area Detection, Vehicle Line Crossing Detection, Vehicle Intrusion Detection, Vehicle Enter Area Detection, Vehicle Exit Area Detection), Tampering Detection, Temperature Detection, Smoking Detection, Fire Detection, Sun-reflection Filter

Audio

Audio Type	2-way, Mic-in, Line-in, Line-out
Audio Compression	G.722.1, G.711, G.726, PCM, MP2L2

Network

Network Protocol & Service	IPv4, IPv6, TCP, UDP, DHCP, PPPoE, HTTP, HTTPS, DNS, DDNS, NTP, RTP, RTSP, RTCP, SRTP, FTP, SFTP, SMTP, IGMP, ICMP, ARP, UPnP, SNMP, QoS, IEEE 802.1X
Ethernet Port	1 x Ethernet (10/100 Base-T), RJ-45 connector
Security	IP address filtering, HTTPS encryption, Password protected user level, IEEE 802.1X network access control

Temperature Measurement

Temperature Measurement Rules	3 types (point, area, line), up to 21 rules in total (10 points, 10 areas, 1 line)
Temperature Range	-20°C ~ 150°C (-4°F ~ 302°F)
Temperature Accuracy	±8°C (14.4°F)

Detection Range

Triggering Analytics Event Notification	(People 1.8x0.5m) 28.8m (Vehicle 1.4x4.0m) 75.6m
Triggering Temperature Notification	(Object 0.2x0.2m) 1.7m (Object 1x1m) 58.3m
Triggering Fire Detection Event Notification	(Object 0.2x0.2m) 43.2m
Triggering Smoking Detection Event Notification	5.4m
Observation Range	Detection: People 150m; Vehicle 460m Recognition: People 38m; Vehicle 112m Identification: People 19m; Vehicle 56m (People: 1.8 x 0.5m) (Vehicle: 1.4 x 4.0m)

Integration

ONVIF Compliant	Yes, Profile G
Web Browser	IE 11, Microsoft Edge, Google Chrome, Firefox

Interface

Serial Port	1 x RS-485
Audio Interface	1/1, 3.5mm Phone Jack
Analog Video Output	1 x BNC connector, for installation only
Digital Input/Output	2/2

General

Power Source	DC 12V, PoE Class 3 (IEEE802.3af)
Power Consumption	8.5 W (DC), 8.5 W (PoE)
Weight	1650g (3.64lb)
Dimensions	(L x W x H): 321.3mm x 106.1mm x 107.0mm (12.65" x 4.18" x 4.21")
Environmental Casing	Weatherproof (IP68), Vandal proof metal casing (IK10)
Corrosion Protection	Optional for project request. Chassis corrosion resistance at the seashore approximately 3 years.
Operating Temperature	-40°C ~ 70°C (-40°F ~ 158°F)
Operating Humidity	≤90% RH, non-condensing
Real-time Clock (RTC)	Yes
Warranty	3 Year(s). For extended warranty offering, see http://www.acti.com/support/warranty

Related Products**Mounting Accessories - Camera Mount**

PMAX-0407	 Corner Mount (for A42x, A42xD, A570, A570-P1, A570-P2, A7xD, A82xD, VMGB-359, VMGB-359-P1)
-----------	--

PMA-0524



Pole Mount (for A46, A421, A422, A423, A425, VMGB-359), supports 2.64" to 5" Poles

Note: Some mounting accessories may need additional accessories for installation. Please check www.acti.com/mountingselector for more information.

Power Supply Accessories - Power Adapter

PPBX-0011



Power Adapter AC 100~240V, with universal connectors for all DC12V powered devices

Power Supply Accessories - PoE Injector

PPOE-0107



High PoE Injector IEEE 802.3at compliant, AC 100~240V, with universal connectors (for A416, A418, B913, B923, B934, Q450, Q75, VMGB-60X, Z37, Z71, Z952)

Network & Storage Peripherals - Data Switch

PPSW-0102



PLANET FGSD-1011HP 8-Port 802.3at PoE Switch (PoE Budget 120W)

PPSW-0108



8-Port Gigabit 802.3at Managed PoE Switch (PoE Budget 120W)

PPSW-0109



8-Port 802.3at Smart Managed PoE Switch (PoE Budget 120W)

PPSW-1101



PLANET GS-4210-24PL4C 24-Port Gigabit 802.3at Managed PoE Switch (PoE Budget 440W)

PPSW-1107



24-port 10/100/1000Mbps PoE, Smart Managed Gigabit Ethernet PoE Switch

PPSW-2105



4-Port 802.3at Smart Managed Gigabit PoE Switch

PPSW-3101



16-Port Gigabit 802.3at Managed PoE Switch (PoE Budget 240W)

PPSW-3103



16-Port 802.3at PoE Switch (PoE Budget 250W)

PPSW-3104



16-Port 802.3at Smart Managed PoE Switch (PoE Budget 250W)

PPSW-3402



16-Port 10/100/1000T 802.3bt PoE + 8-Port 10/100/1000T + 4-Port 10G SFP+ Managed Ethernet Switch

PPSW-4205



24-Port 10/100/1000T 802.3at PoE + 2-Port 100/1000X SFP Managed Switch (PoE Budget 300W)